



Product line-up

Summer 2017



WISENET X
XNB-8000

WISENET X
XNB-6005

WISENET X
XNB-6000

	5MP	2MP	2MP
Resolution	5MP	2MP	2MP
Imaging Device	1/1.8" 6M CMOS	1/1.9" 2M CMOS	1/2.8" 2M CMOS
Video Compression Format	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG
Resolution / Max. Frame Rate	5M / 30fps	2M / 60fps	2M / 60fps
Streaming Capacity	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)
Max. User Access	20 (Unicast)	20 (Unicast)	20 (Unicast)
Min. Illumination	Color: 0.07 Lux B/W: 0.007 Lux	Color: 0.006 Lux B/W: 0.0006 Lux	Color: 0.01 Lux B/W: 0.001 Lux
Video Output	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B
Lens	-	-	-
Angular Field of View	-	-	-
Focus Control	Simple Focus / Manual	Simple Focus / Manual	Simple Focus / Manual
IR Viewable Length	-	-	-
Pan / Tilt / Rotate	-	-	-
Day & Night	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (120dB)	WDR (150dB)	WDR (150dB)
Digital Noise Reduction	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)
Digital Image Stabilization	Support (Built in Gyro sensor)	Support (Built in Gyro sensor)	Support (Built in Gyro sensor)
Video & Audio Analytics	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification
Protocol	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI
Alarm I/O	1 / 1	1 / 1	1 / 1
Audio	Bi-Directional	Bi-Directional	Bi-Directional
Edge Storage	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC
Environment Protection	-	-	-
Operating Temperature	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)
Power	Max. 8.5W (24V AC) Max. 7.5W (12V DC) Max. 8.5W (PoE)	Max. 9W (24V AC) Max. 8W (12V DC) Max. 8.5W (PoE)	Max. 8W (24V AC) Max. 6.5W (12V DC) Max. 7.5W (PoE)
Dimensions (WxHxD) / Weight	73.1 x 66.6 x 147.8mm (2.88" x 2.62" x 5.82") 420g (0.93 lb)	73.1 x 66.6 x 147.8mm (2.88" x 2.62" x 5.82") 420g (0.93 lb)	73.1 x 66.6 x 147.8mm (2.88" x 2.62" x 5.82") 420g (0.93 lb)
Additional Features	DIS with Gyro Sensor, Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	DIS with Gyro Sensor, Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	DIS with Gyro Sensor, Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View



**WISENET X
XNO-8080R**



**WISENET X
XNO-8020R/8030R/8040R**



**WISENET X
XNO-6120R**



**WISENET X
XNO-6085R**



**WISENET X
XNO-6080R**



**WISENET X
XNO-6010R/6020R**

	5MP	5MP	2MP	2MP	2MP	2MP	
VIDEO	Resolution	5MP	5MP	2MP	2MP	2MP	2MP
	Imaging Device	1/1.8" 6M CMOS	1/1.8" 6M CMOS	1/2.8" 2M CMOS	1/1.9" 2M CMOS	1/2.8" 2M CMOS	1/2.8" 2M CMOS
	Video Compression Format	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG
	Resolution / Max. Frame Rate	5M / 30fps	5M / 30fps	2M / 60fps	2M / 60fps	2M / 60fps	2M / 60fps
	Streaming Capacity	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)
	Max. User Access	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)
	Min. Illumination	Color: 0.07 Lux B/W: 0 Lux (IR LED on)	Color: 0.16 Lux B/W: 0 Lux (IR LED on)	Color: 0.03 Lux B/W: 0 Lux (IR LED on)	Color: 0.004 Lux B/W: 0 Lux (IR LED on)	Color: 0.015 Lux B/W: 0 Lux (IR LED on)	Color: 0.055 Lux (XNO-6010R), 0.01 Lux (XNO-6020R) B/W: 0 Lux (IR LED on)
	Video Output	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B
	Lens	3.7 ~ 9.4mm (2.5x) motorized V/F (F1.2)	3.7mm fixed (F1.6) (XNO-8020R) 4.6mm fixed (F1.6) (XNO-8030R) 7.0mm fixed (F1.6) (XNO-8040R)	5.2 ~ 62.4mm (Optical 12X)	4.1 ~ 16.4mm (Optical 4x)	2.8 ~ 12mm (4.3x) motorized V/F (F1.4)	2.4mm fixed (F2.0) (XNO-6010R) 4mm fixed (F1.2) (XNO-6020R)
	Angular Field of View	H : 100.2° (Wide) ~ 38.7° (Tele) / V : 72.7° (Wide) ~ 29.0° (Tele) / D : 132.0° (Wide) ~ 48.6° (Tele)	H : 97.5° / V : 71.9° / D : 126.2° (XNO-8020R) H : 77.9° / V : 57.9° / D : 98.7° (XNO-8030R) H : 50.7° / V : 37.8° / D : 63.8° (XNO-8040R)	H : 54.58° (Wide) ~ 5.30° (Tele) / V : 32.19° (Wide) ~ 3.00° (Tele) / D : 61.40° (Wide) ~ 6.06° (Tele)	H : 100° (Wide) ~ 26.2° (Tele) / V : 54° (Wide) ~ 14.5° (Tele) / D : 116° (Wide) ~ 32.0° (Tele)	H : 119.5° (Wide) ~ 27.9° (Tele) / V : 62.8° (Wide) ~ 15.7° (Tele) / D : 142.1° (Wide) ~ 32.0° (Tele)	H : 139.0° / V : 73.0° / D : 167.0° (XNO-6010R) H : 88.6° / V : 47.5° / D : 104.8° (XNO-6020R)
Focus Control	Simple Focus (motorized V/F) / Manual	-	Auto / Manual / One shot AF	Simple Focus (motorized V/F) / Manual	Simple Focus (motorized V/F) / Manual	-	
OPERATIONAL	IR Viewable Length	50m (164.04ft)	30m (98.43ft)	70m (229.66ft)	70m (229.66ft)	50m (164.04ft)	20m (65.61ft) (XNO-6010R) / 30m (98.43ft) (XNO-6020R)
	Pan / Tilt / Rotate	-	-	-	-	-	-
	Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)
	Backlight Compensation	WDR (120dB)	WDR (120dB)	WDR (150dB)	WDR (150dB)	WDR (150dB)	WDR (150dB)
	Digital Noise Reduction	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)
	Digital Image Stabilization	Support	Support	Support	Support (Built in Gyro sensor)	Support	Support
	Video & Audio Analytics	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification, Heatmap, People counting, Queue Management	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Sound Classification	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification, Heatmap, People counting, Queue Management
	Protocol	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S&G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI
	Alarm I/O	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1
	Audio	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional
Edge Storage	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	
Environment Protection	IP67, IP66, NEMA 4X, IK10	IP67, IP66, NEMA 4X, IK10	IP67, IP66, NEMA 4X, IK10	IP67, IP66, NEMA 4X, IK10	IP67, IP66, NEMA 4X, IK10	IP67, IP66, NEMA 4X, IK10	
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -20°C (-4°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-40°C ~ +55°C (-40°F ~ +131°F) (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	
Power	Max. 14.5W (24V AC) Max. 12.5W (12V DC) Max. 12.95W (PoE)	Max. 8.8W (12V DC) Max. 9.8W (PoE)	Max. 14.5W (24V AC) Max. 12.5W (12V DC) Max. 12.95W (PoE)	Max. 14.5W (24V AC) Max. 11.5W (12V DC) Max. 12.95W (PoE)	Max. 15W (24V AC) Max. 12W (12V DC) Max. 12.95W (PoE)	Max. 7.8W (12V DC) Max. 8.8W (PoE)	
Dimensions (WxHxD) / Weight	Ø91.0 x 368.6mm (Ø3.58" x 14.51") (Without Sunshield) 2.18Kg (4.81 lb)	Ø120.0 x 296.0mm (Ø4.72" x 11.65") (Without Sunshield) 1.3Kg (2.87 lb)	Ø91.0 x 368.6mm (Ø3.58" x 14.51") 2.18Kg (4.81 lb)	Ø91.0 x 368.6mm (Ø3.58" x 15.30") 2.35Kg (5.18 lb)	Ø91.0 x 368.6mm (Ø3.58" x 14.51") (Without Sunshield) 2.18Kg (4.81 lb)	Ø70.0 x 296.0mm (Ø2.76" x 11.65") (Without Sunshield) 1.3Kg (2.87 lb)	
Additional Features	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	DIS with Gyro Sensor, Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	



WISENET X
XND-8080RV



WISENET X
XND-8020R/8030R/8040R



WISENET X
XND-8020F



WISENET X
XNF-8010R/8010RV/8010RVM



WISENET X
XND-6085V



WISENET X
XND-6080V

	5MP	5MP	5MP	4.2MP	2MP	2MP
Resolution	5MP	5MP	5MP	4.2MP	2MP	2MP
Imaging Device	1/1.8" 6M CMOS	1/1.8" 6M CMOS	1/1.8" 6M CMOS	1/1.8" 6M CMOS	1/1.9" 2M CMOS	1/2.8" 2M CMOS
Video Compression Format	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG
Resolution / Max. Frame Rate	5M / 30fps	5M / 30fps	5M / 30fps	4M / 30fps	2M / 60fps	2M / 60fps
Streaming Capacity	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)
Max. User Access	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)
Min. Illumination	Color: 0.07 Lux B/W: 0 Lux (IR LED on)	Color: 0.16 Lux B/W: 0 Lux (IR LED on)	Color: 0.16 Lux B/W: 0.16 Lux	Color: 0.07 Lux B/W: 0 Lux (IR LED on)	Color: 0.004 Lux B/W: 0.0004 Lux	Color: 0.015 Lux B/W: 0.0015 Lux
Video Output	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	Micro USB type B	CVBS 1.0Vpp, DIP connector type	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B
Lens	3.9 ~ 9.4mm (2.4x) motorized V/F (F1.3)	3.7mm fixed (F1.6) (XND-8020R) 4.6mm fixed (F1.6) (XND-8030R) 7.0mm fixed (F1.6) (XND-8040R)	3.7mm fixed (F1.6)	1.6mm fixed (F1.6)	4.1 ~ 16.4mm (Optical 4X)	2.8 ~ 12mm (4.3x) motorized V/F (F1.4)
Angular Field of View	H: 92.1° (Wide) ~ 38.7° (Tele) / V: 67.2° (Wide) ~ 29.0° (Tele) / D: 119.9° (Wide) ~ 48.6° (Tele)	H: 97.5° / V: 71.9° / D: 126.2° (XND-8020R) H: 77.9° / V: 57.9° / D: 98.7° (XND-8030R) H: 50.7° / V: 37.8° / D: 63.8° (XND-8040R)	H: 97.5° / V: 71.9° / D: 126.2°	H: 187° / V: 187° / D: 187°	H: 100° (Wide) ~ 26.2° (Tele) / V: 54° (Wide) ~ 14.5° (Tele) / D: 116° (Wide) ~ 30.0° (Tele)	H: 119.5° (Wide) ~ 27.9° (Tele) / V: 62.8° (Wide) ~ 15.7° (Tele) / D: 142.1° (Wide) ~ 32.0° (Tele)
Focus Control	Simple Focus (motorized V/F) / Manual	-	Manual	Simple focus / Manual	Simple Focus (motorized V/F) / Manual	Simple Focus (motorized V/F) / Manual
IR Viewable Length	30m (98.43ft)	30m (98.43ft)	-	15m (49.21ft)	-	-
Pan / Tilt / Rotate	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 355° / 0° ~ 47° / 0° ~ 353°	-	±185° / ±73° / ±110° (PTRZ)	0° ~ 354° / 0° ~ 67° / 0° ~ 355°
Day & Night	True (ICR)	True (ICR)	Auto (Electrical)	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (150dB)	WDR (150dB)
Digital Noise Reduction	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)
Digital Image Stabilization	Support	Support	Support	Support	Support (Built in Gyro sensor)	Support
Video & Audio Analytics	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification, Heatmap, People counting, Queue Management	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification, Heatmap, People counting, Queue Management	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification, Heatmap, People counting, Queue Management	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification
Protocol	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI
Alarm I/O	1 / 1	1 / 1	-	1 / 1	1 / 1	1 / 1
Audio	Bi-Directional	Bi-Directional	Uni-Directional	Bi-Directional	Bi-Directional	Bi-Directional
Edge Storage	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC
Environment Protection	IK08	IK08	-	-	IP51, IK08	IK08
Operating Temperature	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-10°C ~ +55°C (+14°F ~ +131°F)
Power	Max. 9W (12V DC) Max. 10W (PoE)	Max. 8W (12V DC) Max. 9W (PoE)	Max. 4.7W	TBD	TBD	Max. 6W (12V DC) Max. 6.5W (PoE)
Dimensions (WxHxD) / Weight	Ø140.8 x 113.0mm (Ø5.54" x 4.45") 628g (1.39 lb) (XND-8080R) 732g (1.61 lb) (XND-8080RV)	Ø110.0 x 90.0mm (Ø4.33" x 3.54") 365g (0.80 lb)	Ø98.9 x 129mm (Ø3.89" x 5.08") 275g (0.61 lb)	TBD	TBD	Ø140.8 x 113.0mm (Ø5.54" x 4.45") 714g (1.57 lb)
Additional Features	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced analytics, Sound classification (Explosion, Gunshot, Glass Breakage, Scream etc)	M12 Connector(XNF-8010RVM), Built-in MIC, On Board Dewarping, Handover, WiseStream II, Heatmap, People counting	DIS with Gyro Sensor, Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View



WISENET X
XND-6080RV



WISENET X
XND-6011F



WISENET X
XND-6010



WISENET X
XND-6020R



WISENET X
XNV-8080R



WISENET X
XNV-8020R/8030R/8040R



WISENET X
XNV-6120/6120R



WISENET X
XNV-6080R

	2MP	2MP	2MP	2MP	5MP	5MP	2MP	2MP
Resolution	2MP	2MP	2MP	2MP	5MP	5MP	2MP	2MP
Imaging Device	1/2.8" 2M CMOS	1/2.8" 2M CMOS	1/2.8" 2M CMOS	1/2.8" 2M CMOS	1/1.8" 6M CMOS	1/1.8" 6M CMOS	1/2.8" 2M CMOS	1/2.8" 2M CMOS
Video Compression Format	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG
Resolution / Max. Frame Rate	2M / 60fps	2M / 60fps	2M / 60fps	2M / 60fps	5M / 30fps	5M / 30fps	2M / 60fps	2M / 60fps
Streaming Capacity	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)
Max. User Access	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)
Min. Illumination	Color: 0.015 Lux B/W: 0 Lux (IR LED on)	Color: 0.055 Lux B/W: 0.055 Lux	Color: 0.055 Lux B/W: 0.055 Lux	Color: 0.015 Lux B/W: 0 Lux (IR LED on)	Color: 0.07 Lux B/W: 0 Lux (IR LED on)	Color: 0.2 Lux B/W: 0 Lux (IR LED on)	Color: 0.03 Lux B/W: 0.003 Lux (XNV-6120) Color: 0.03 Lux B/W: 0 Lux (IR LED on) (XNV-6120R)	Color: 0.015 Lux B/W: 0 Lux (IR LED on)
Video Output	CVBS 1.0Vpp, Micro USB type B	Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B
Lens	2.8 ~ 12mm (4.3x) motorized V/F (F1.4)	2.8mm fixed (F2.0)	2.4mm fixed (F2.0)	4mm fixed (F1.4)	3.9 ~ 9.4mm (2.4x) motorized V/F (F1.3)	3.7mm fixed (F1.6) (XNV-8020R) 4.6mm fixed (F1.6) (XNV-8030R) 7.0mm fixed (F1.6) (XNV-8040R)	5.2 ~ 62.4mm (Optical 12x)	2.8 ~ 12mm (4.3x) motorized V/F (F1.4)
Angular Field of View	H: 119.5°(Wide) ~ 27.9°(Tele) / V: 62.8°(Wide) ~ 15.7°(Tele) / D: 142.1°(Wide) ~ 32.0°(Tele)	H: 112° / V: 62° / D: 130°	H: 139.0° / V: 73.0° / D: 167.0°	H: 88.6° / V: 47.5° / D: 104.8°	H: 92.1°(Wide) ~ 38.7°(Tele) / V: 67.2°(Wide) ~ 29.0°(Tele) / D: 119.9°(Wide) ~ 48.6°(Tele)	H: 97.5° / V: 71.9° / D: 126.2° (XNV-8020R) H: 77.9° / V: 57.9° / D: 98.7° (XNV-8030R) H: 50.7° / V: 37.8° / D: 63.8° (XNV-8040R)	H: 54.58°(Wide) ~ 5.30°(Tele) / V: 32.19°(Wide) ~ 3.00°(Tele) / D: 61.40°(Wide) ~ 6.06°(Tele)	H: 119.5°(Wide) ~ 27.9°(Tele) / V: 62.8°(Wide) ~ 15.7°(Tele) / D: 142.1°(Wide) ~ 32.0°(Tele)
Focus Control	Simple Focus (motorized V/F) / Manual	Manual	-	-	Simple Focus (motorized V/F) / Manual	-	Auto / Manual / One shot AF	Simple Focus (motorized V/F) / Manual
IR Viewable Length	30m (98.43ft)	-	-	30m (98.43ft)	50m (164.04ft)	30m (98.43ft)	70m (229.66ft) (XNV-6120R)	50m (164.04ft)
Pan / Tilt / Rotate	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 355° / 0° ~ 47° / 0° ~ 353°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 75° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°
Day & Night	True (ICR)	Auto (Electrical)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (150dB)	WDR (150dB)	WDR (150dB)	WDR (150dB)	WDR (120dB)	WDR (120dB)	WDR (150dB)	WDR (150dB)
Digital Noise Reduction	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)
Digital Image Stabilization	Support	Support	Support	Support	Support	Support	Support (Built in Gyro sensor)	Support
Video & Audio Analytics	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification, Heatmap, People counting, Queue Management	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification, Heatmap, People counting, Queue Management	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification, Heatmap, People counting, Queue Management	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification, Heatmap, People counting, Queue Management	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification
Protocol	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI
Alarm I/O	1 / 1	-	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1
Audio	Bi-Directional	Uni-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional
Edge Storage	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC
Environment Protection	IK08	IK08	IK08	IK08	IP67, IP66, NEMA 4X, IK10	IP67, IP66, IK10	IP67, IP66, NEMA 4X, IK10	IP67, IP66, NEMA 4X, IK10
Operating Temperature	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-40°C ~ +55°C (-40°F ~ +131°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-40°C ~ +55°C (-40°F ~ +131°F)
Power	Max. 9W (12V DC) Max. 10W (PoE)	Max. 4.7W	Max. 5.5W (12V DC) Max. 6W (PoE)	Max. 8W (12V DC) Max. 9W (PoE)	Max. 14W (24V AC) Max. 11.5W (12V DC) Max. 12.95W (PoE)	Max. 8W (12V DC) Max. 9W (PoE)	Max 8.2W (24V AC), Max 7W (12V DC), Max 7.8W (PoE) (XNV-6120) Max 14W (24V AC), Max 11.5W (12V DC), Max 12.95W (PoE) (XNV-6120R)	Max. 14W (24V AC) Max. 11.5W (12V DC) Max. 12.95W (PoE)
Dimensions (WxHxD) / Weight	Ø140.8 x 113.0mm (Ø5.54" x 4.45") 724g (1.60 lb)	Ø98.9 x 129mm (Ø4.33" x 5.08") 275g (0.61 lb)	Ø110.0 x 90.0mm (Ø4.33" x 3.54") 365g (0.80 lb)	Ø110.0 x 90.0mm (Ø4.33" x 3.54") 380g (0.84 lb)	Ø160.0 x 118.5mm (Ø6.3" x 4.67") 1.01Kg (2.23 lb)	Ø120.0 x 97.5mm (Ø4.72" x 3.84") 625g (1.38 lb)	Ø160.0 x 128.5mm (Ø6.3" x 5.06") 995g (2.19 lb)	Ø160.0 x 118.5mm (Ø6.3" x 4.67") 995g (2.19 lb)
Additional Features	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced analytics, Sound classification (Explosion, Gunshot, Glass Breakage, Scream etc)	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View



	WISENET X XNV-6085	WISENET X XNV-6080	WISENET X XNV-6011	WISENET X XNV-6010	WISENET X XNV-6020R	WISENET X XNP-6040H	WISENET X XNP-6120H	WISENET X XNP-6370RH
Resolution	2MP	2MP	2MP	2MP	2MP	2MP	2MP	2MP
Imaging Device	1/1.9" 2M CMOS	1/2.8" 2M CMOS	1/2.8" 2M CMOS	1/2.8" 2M CMOS	1/2.8" 2M CMOS	1/2.8" 2M CMOS	1/2.8" 2M CMOS	1/1.9" 2M CMOS
Video Compression Format	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG
Resolution / Max. Frame Rate	2M / 60fps	2M / 60fps	2M / 60fps	2M / 60fps	2M / 60fps	2M / 60fps	2M / 60fps	2M / 60fps
Streaming Capacity	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 3 Profiles)
Max. User Access	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)	20 (Unicast)	15 (Unicast)
Min. Illumination	Color : 0.005 Lux B/W : TBD	Color : 0.015 Lux B/W : 0.0015 Lux	Color : 0.055 Lux B/W : 0.0055 Lux	Color : 0.055 Lux B/W : 0.0055 Lux	Color : 0.015 Lux B/W : 0 Lux (IR LED on)	Color : 0.015 Lux B/W : 0.0015 Lux	Color : 0.03 Lux B/W : 0.003 Lux	Color : 0.05 Lux B/W : 0 Lux (IR LED on)
Video Output	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp, Micro USB type B	CVBS 1.0Vpp
Lens	4.1 ~ 16.4mm (Optical 4X)	2.8 ~ 12mm (4.3x) motorized V/F (F1.4)	2.8mm fixed (F2.0)	2.4mm fixed (F2.0)	4mm fixed (F1.4)	2.8 ~ 12mm (optical 4.3x)	5.2 ~ 62.4mm (Optical 12X)	6 ~ 222mm (IR Corrected Optical 37x) F1.5(Wide) / F4.6(Tele)
Angular Field of View	H : 100° (Wide) ~ 26.2° (Tele) / V : 54° (Wide) ~ 14.5° (Tele) / D : 116° (Wide) ~ 30.0° (Tele)	H : 119.5° (Wide) ~ 27.9° (Tele) / V : 62.8° (Wide) ~ 15.7° (Tele) / D : 142.1° (Wide) ~ 32.0° (Tele)	H : 112° / V : 62° / D : 130°	H : 139.0° / V : 73.0° / D : 167.0°	H : 88.6° / V : 47.5° / D : 104.8°	H : 119.5° (Wide) ~ 27.9° (Tele)	H : 54.58° (Wide) ~ 5.30° (Tele) / V : 32.19° (Wide) ~ 3.00° (Tele)	H : 59.3° (Wide) ~ 1.9° (Tele) / V : 35.8° (Wide) ~ 1.1° (Tele)
Focus Control	Simple Focus (motorized V/F) / Manual	Simple Focus (motorized V/F) / Manual	Manual	-	-	Auto / Manual / One shot AF	Auto / Manual / One shot AF	AF / One-shot AF / Manual
IR Viewable Length	-	-	-	-	30m (98.43ft)	-	-	350m (1,148.29ft)
Pan / Tilt / Rotate	±185° / ±73° / ±110° (PTRZ)	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 353° / 0° ~ 59° / 0° ~ 353°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 355° / 0° ~ 90°	360° Endless / 190° (-5° ~ 185°)	360° Endless / 190° (-5° ~ 185°) / -
Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (150dB)	WDR (150dB)	WDR (150dB)	WDR (150dB)	WDR (150dB)	WDR (150dB)	WDR (150dB)	WDR (120dB)
Digital Noise Reduction	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNR (2D+3D Noise Filter)
Digital Image Stabilization	Support (Built in Gyro sensor)	Support	Support	Support	Support	Support (Built in Gyro sensor)	Support (Built in Gyro sensor)	Support (Built in Gyro sensor)
Video & Audio Analytics	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Face Detection, Motion Detection, Digital Auto Tracking, People Counting, Heatmap, Queue management	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification, Heatmap, People counting, Queue Management	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Motion Detection, Face Detection, Digital Auto Tracking, Sound Classification, Heatmap, People counting, Queue Management	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter/Exit, (Dis)Appear, Motion Detection, Face Detection, Audio Detection, Face Detection, Motion Detection Sound Classification	Tampering, Loitering, Directional Detection, Fog Detection, Virtual Line, Enter/Exit, (Dis)Appear, Audio Detection, Face Detection, Motion Detection, Sound Classification	Tampering, Crossing, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection
Protocol	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI
Alarm I/O	1 / 1	1 / 1	-	1 / 1	1 / 1	1 / 1	1 / 1	4 / 2 (Relay)
Audio	Bi-Directional	Bi-Directional	-	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional
Edge Storage	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC
Environment Protection	IP67, IP66, NEMA 4X	IP67, IP66, NEMA 4X, IK10	IP66, IK10, NEMA4X	IP67, IP66, NEMA 4X, IK10	IP67, IP66, IK10	IP66, IK10	IP66, IK10	IP66, IK10
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-40°C ~ +55°C (-40°F ~ +131°F)	-30°C ~ +55°C (-22°F ~ +131°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-30°C ~ +55°C (-22°F ~ +131°F)	-50°C ~ +55°C (-58°F ~ +131°F)
Power	Max. 15W (24V AC) Max. 12W (12V DC) Max. 12.95W (PoE)	Max. 8.2W (24V AC) Max. 7W (12V DC) Max. 7.8W (PoE)	Max. 6.5W (PoE)	Max. 5.5W (12V DC) Max. 6W (PoE)	Max. 8W (12V DC) Max. 9W (PoE)	Max. 10W (12V DC) Max. 12.9W (PoE)	Max. 12W (12V DC) Max. 12W (PoE)	Max. 60.0W / 90.0W - Heater off / on, IR on (24V AC)
Dimensions (WxHxD) / Weight	TBD	Ø160.0 x 118.5mm (Ø6.3" x 4.67") 985g (2.17 lb)	Ø112.8 x 63.7mm (Ø4.44" x 2.51") 420g (0.93 lb)	Ø120.0 x 97.5mm (Ø4.72" x 3.84") 625g (1.38 lb)	Ø120.0 x 97.5mm (Ø4.72" x 3.84") 615g (1.36 lb)	Ø136 x 106mm (Ø5.35" x 4.17") 760g (1.68 lb)	Ø168.0 x 161.5mm (Ø6.61" x 6.36") 1.9kg (4.19 lb)	Ø236.9 x 407.7mm (Ø9.33" x 16.05") 7.1kg (15.65 lb)
Additional Features	Handover, WiseStream II, Advanced analytics, Sound classification (Explosion, Gunshot, Glass Breakage, Scream etc) Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	Handover, WiseStream II, Advanced Video Analytics, Sound Classification (Explosion, Gunshot, Glass Breakage, Scream etc), Hallway View	WiseStream II, Advanced analytics, Auto Tracking Sound classification (Explosion, Gunshot, Glass Breakage, Scream etc)	WiseStream II, Advanced analytics, Auto Tracking Sound classification (Explosion, Gunshot, Glass Breakage, Scream etc)	Handover, Defog, WiseStream, Auto tracking



WISENET P
PNO-9080R



WISENET P
PND-9080R



WISENET P
PNV-9080R



WISENET P
PNM-9081VQ

New



WISENET P
PNM-9080VQ

New



WISENET P
PNM-9020V



WISENET P
PNF-9010R/9010RV/9010RVM



WISENET P
PNP-9200RH

	12MP	12MP	12MP	20MP	8MP	7.3MP	9MP	8MP
Resolution	12MP	12MP	12MP	20MP	8MP	7.3MP	9MP	8MP
Imaging Device	1/1.7" 12.4M CMOS	1/1.7" 12.4M CMOS	1/1.7" 12.4M CMOS	1/1.8" 6M CMOS x 4	1/2.8" 2.38M CMOS x 4	7.3M (2M x 4)	1/1.7" 12.4M CMOS	1/2.5" 8M CMOS
Video Compression Format	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG
Resolution / Max. Frame Rate	12M / 20fps, 8M / 30fps	12M / 20fps, 8M / 30fps	12M / 20fps, 8M / 30fps	4ea x 5M / 30fps	4ea x 2M / 60fps	7.3M / 30fps (H.265, H.264)	12M / 20fps, 9M / 25fps	8M / 30fps (H.265, H.264)
Streaming Capacity	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 40 Profiles)	Multiple (Up to 40 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)
Max. User Access	15 (Unicast)	15 (Unicast)	15 (Unicast)	20 (Unicast)	20 (Unicast)	15 (Unicast)	15 (Unicast)	15 (Unicast)
Min. Illumination	Color: 0.3 Lux B/W: 0 Lux (IR LED on)	Color: 0.3 Lux B/W: 0 Lux (IR LED on)	Color: 0.3 Lux B/W: 0 Lux (IR LED on)	Color: 0.07 Lux B/W: 0.007 Lux	Color: 0.015 Lux B/W: 0.0015 Lux	Color: 0.3 Lux B/W: 0.03 Lux	Color: 0.3 Lux B/W: 0 Lux (IR LED on)	Color: 0.1 Lux B/W: 0 Lux (IR LED on)
Video Output	CVBS 1.0Vpp, DIP Connector Type	CVBS 1.0Vpp, DIP Connector Type	CVBS 1.0Vpp, DIP Connector Type	CVBS 1.0Vpp (selectable CVBS per channel)	CVBS 1.0Vpp (selectable CVBS per channel)	-	CVBS 1.0Vpp, DIP Connector Type	CVBS 1.0Vpp
Lens	4.5 ~ 10mm (2.2x) motorized V/F (F1.6)	4.5 ~ 10mm (2.2x) motorized V/F (F1.6)	4.5 ~ 10mm (2.2x) motorized V/F (F1.6)	3.6 ~ 9.4mm (2.6x) motorized V/F	2.8 ~ 12mm (4.3x) motorized V/F	3.6mm fixed	2.1mm fixed (F2.2)	4.8 ~ 96mm (IR Corrected Optical 20x) F1.8(Wide) / F3.6(Tele)
Angular Field of View	[4096 x 2160] H: 100.3°(Wide) ~ 45.6°(Tele) / V: 49.7°(Wide) ~ 24.0°(Tele) [3840 x 2160] H: 92.3°(Wide) ~ 42.6°(Tele) / V: 49.7°(Wide) ~ 24.0°(Tele)	[4096 x 2160] H: 100.3°(Wide) ~ 45.6°(Tele) / V: 49.7°(Wide) ~ 24.0°(Tele) [3840 x 2160] H: 92.3°(Wide) ~ 42.6°(Tele) / V: 49.7°(Wide) ~ 24.0°(Tele)	[4096 x 2160] H: 100.3°(Wide) ~ 45.6°(Tele) / V: 49.7°(Wide) ~ 24.0°(Tele) [3840 x 2160] H: 92.3°(Wide) ~ 42.6°(Tele) / V: 49.7°(Wide) ~ 24.0°(Tele)	H: 102.5°(Wide) ~ 38.7°(Tele) / V: 74.2°(Wide) ~ 29.0°(Tele) / D: 135.5°(Wide) ~ 48.6°(Tele)	H: 119.5°(Wide) ~ 27.9°(Tele) / V: 62.8°(Wide) ~ 15.7°(Tele) / D: 142.1°(Wide) ~ 32.0°(Tele)	[Total 4 Sensor] H: 180° / V: 84°	H: 180.0° / V: 180.0° / D: 180.0°	H: 65.1°(Wide) ~ 3.8°(Tele) / V: 38.4°(Wide) ~ 2.2°(Tele)
Focus Control	Simple Focus (motorized V/F) / Manual	Simple Focus (motorized V/F) / Manual	Simple Focus (motorized V/F) / Manual	Simple focus (motorized V/F) / Manual	Simple focus (motorized V/F) / Manual	-	Simple Focus	AF / One-shot AF
IR Viewable Length	40m (131.23ft)	30m (98.43ft)	40m (131.23ft)	-	-	-	15m (49.21ft)	200m (656.17ft)
Pan / Tilt / Rotate	-	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	Quad mode: ±30° / 10° ~ 41° / ±90° Center mode: ±60° / 10° ~ 41°, 10° ~ 90°(CH2/Center) / ±90°	Quad mode: ±30° / 10° ~ 41° / ±90° Center mode: ±60° / 10° ~ 41°, 10° ~ 90°(CH2/Center) / ±90°	0° ~ 355° / 0° ~ 73° / -	-	360° Endless / 190° (-5° ~ 185°) / -
Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (150dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)
Digital Noise Reduction	SSNR	SSNR	SSNR	SSNRV (2D+3D Noise Filter)	SSNRV (2D+3D Noise Filter)	SSNRIII (2D+3D Noise Filter)	SSNR	SSNR
Digital Image Stabilization	-	-	-	Support (Built in Gyro sensor)	Support (Built in Gyro sensor)	-	-	Support
Intelligent Video Analytics	Tampering (Scene change), Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Defocus Detection, Digital Auto Tracking - with Metadata	Tampering (Scene change), Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Defocus Detection, Digital Auto Tracking - with Metadata	Tampering (Scene change), Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Defocus Detection, Digital Auto Tracking - with Metadata	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter/Exit, (Dis)Appear, Motion Detection	Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter/Exit, (Dis)Appear, Motion Detection	Tampering (Scene change), Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Defocus Detection, Digital Auto Tracking - with Metadata	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Defocus Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Defocus Detection - with Metadata
Protocol	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF profile S, SUNAPI	ONVIF profile S, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI
Alarm I/O	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	4 / 2 (Relay)
Audio	Bi-Directional	Bi-Directional	Bi-Directional	-	-	Bi-Directional	Bi-Directional	Bi-Directional
Edge Storage	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, Local PC	SD/SDHC/SDXC, Local PC	SD/SDHC/SDXC, NAS, Local PC	Micro SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC
Environment Protection	IP66, IK10	IK08	IP66, IP67, IK10	IP66, IK10	IP66, IK10	IP66, IK10	IK10 (PNF-9010R), IP66, IK10 (PNF-9010RV/9010RVM)	IP66, IK10
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (14°F)	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-40°C ~ +55°C (-40°F ~ +131°F)	-40°C ~ +55°C (-40°F ~ +131°F)	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-10°C ~ +55°C (+14°F ~ +131°F) (PNF-9010R) -40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F) (PNF-9010RV/9010RVM)	-50°C ~ +55°C (-58°F ~ +131°F)
Power	Max. 12.43W / 14.08W - Heater on (24V AC) Max. 11.77W / 12.95W - Heater on (12V DC) Max. 10.43W / 11.55W - Heater on (PoE)	Max. 9.5W (12V DC) Max. 10.5W (PoE)	Max. 12.43W / 14.08W - Heater on (24V AC) Max. 11.77W / 12.95W - Heater on (12V DC) Max. 10.43W / 11.55W - Heater on (PoE)	Max. 28.8W (12V DC) Max. 33.6W (HPoE)	Max. 21.6W (12V DC) Max. 25.5W (PoE+)	Max. 21.0W - Heater on (12V DC) Max. 25.5W - Heater on (PoE+)	Max. 11W (12V DC), Max. 12W (PoE) (PNF-9010R) Max. 12W (12V DC), Max. 12.95W (PoE) (PNF-9010RV/RVM)	Max. 60.0W / 90.0W - Heater off / on, IR on (24V AC)
Dimensions (WxHxD) / Weight	82.4 x 87.0 x 348.3mm (3.24" x 3.43" x 13.71") (Without Sunshield) 1.4Kg (3.09 lb)	Ø140.8 x 113.0mm (Ø5.54" x 4.45") 610g (1.34 lb)	Ø160.0 x 118.5mm (Ø6.3" x 4.67") 990g (2.18 lb)	Ø314 x 152mm (Ø12.36" x 5.98") 4.89kg (10.78 lb)	Ø314 x 152mm (Ø12.36" x 5.98") 4.83kg (10.65 lb)	Ø199.0 x 143.5mm (Ø7.83" x 5.65") 2.03Kg (4.48 lb)	Ø146.0 x 63.4mm (Ø5.75" x 2.5") 805g (1.77 lb) (PNF-9010R), 810g (1.79 lb) (PNF-9010RV), 815g (1.8 lb) (PNF-9010RVM)	Ø236.9 x 407.7mm (Ø9.33" x 16.05") 7.1Kg (15.65 lb)
Additional Features	Handover, Hallway View, P-Iris, Defog, WiseStream	Handover, Hallway View, P-Iris, Defog, WiseStream	Handover, Hallway View, P-Iris, Defog, WiseStream	Multidirectional camera, WiseStream II	Multidirectional camera, WiseStream II	Handover, Lens Distortion Correction, Multi Sensor, WiseStream	M12 Connector (PNF-9010RVM), Built-in mic, On Board Dewarping, Handover, WiseStream, Heatmap, People Counting	Handover, Defog, Auto tracking, WiseStream



WISENET Q
QNO-7080R



WISENET Q
QNO-7010R/7020R/7030R



WISENET Q
QNO-6070R



WISENET Q
QNO-6010R/6020R/6030R



WISENET Q
QND-7080R



WISENET Q
QND-7010R/7020R/7030R



WISENET Q
QND-6070R



WISENET Q
QND-6010R/6020R/6030R

	4MP	4MP	2MP	2MP	4MP	4MP	2MP	2MP
Resolution	4MP	4MP	2MP	2MP	4MP	4MP	2MP	2MP
Imaging Device	1/3" 4M CMOS	1/3" 4M CMOS	1/2.9" 2.19M CMOS	1/2.9" 2.19M CMOS	1/3" 4M CMOS	1/3" 4M CMOS	1/2.9" 2.19M CMOS	1/2.9" 2.19M CMOS
Video Compression Format	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG
Resolution / Max. Frame Rate	4M / 20fps, 2M / 30fps	4M / 20fps, 2M / 30fps	2M / 30fps	2M / 30fps	4M / 20fps, 2M / 30fps	4M / 20fps, 2M / 30fps	2M / 30fps	2M / 30fps
Streaming Capacity	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)
Max. User Access	6 (Unicast)	6 (Unicast)	6 (Unicast)	6 (Unicast)	6 (Unicast)	6 (Unicast)	6 (Unicast)	6 (Unicast)
Min. Illumination	Color 0.15 Lux B/W: 0 Lux (IR LED on)	Color: 0.5 Lux (QNO-7010R), 0.4 Lux (QNO-7020R), 0.3 Lux (QNO-7030R) B/W: 0 Lux (IR LED on)	Color 0.095 Lux B/W: 0 Lux (IR LED on)	Color: 0.15 Lux B/W: 0 Lux (IR LED on)	Color 0.15 Lux B/W: 0 Lux (IR LED on)	Color: 0.5 Lux (QND-7010R), 0.4 Lux (QND-7020R), 0.3 Lux (QND-7030R) B/W: 0 Lux (IR LED on)	Color 0.095 Lux B/W: 0 Lux (IR LED on)	Color: 0.15 Lux B/W: 0 Lux (IR LED on)
Video Output	-	-	-	-	-	-	-	-
Lens	2.8 ~ 12mm (4.3x) motorized V/F (F1.4)	2.8mm fixed (F2.0) (QNO-7010R) 3.6mm fixed (F2.2) (QNO-7020R) 6mm fixed (F2.2) (QNO-7030R)	2.8 ~ 12mm (4.3x) Manual V/F (F1.4)	2.8mm fixed (F2.0) (QNO-6010R) 3.6mm fixed (F1.8) (QNO-6020R) 6mm fixed (F1.8) (QNO-6030R)	2.8 ~ 12mm (4.3x) motorized V/F (F1.4)	2.8mm fixed (F2.2) (QND-7010R) 3.6mm fixed (F2.2) (QND-7020R) 6mm fixed (F2.2) (QND-7030R)	2.8 ~ 12mm (4.3x) Manual V/F (F1.4)	2.8mm fixed (F2.0) (QND-6010R) 3.6mm fixed (F1.8) (QND-6020R) 6mm fixed (F1.8) (QND-6030R)
Angular Field of View	H: 109.7° (Wide) ~ 26.0° (Tele) / V: 60.8° (Wide) ~ 15.2° (Tele) / D: 131.3° (Wide) ~ 30.1° (Tele)	H: 111.0° / V: 63.0° / D: 133.0° (QNO-7010R) H: 81.0° / V: 45.0° / D: 95.0° (QNO-7020R) H: 53.0° / V: 31.0° / D: 62.0° (QNO-7030R)	H: 103.8° (Wide) ~ 32.4° (Tele) / V: 53.7° (Wide) ~ 18.4° (Tele) / D: 121.9° (Wide) ~ 37.1° (Tele)	H: 116.0° / V: 62.0° / D: 137.0° (QNO-6010R) H: 86.48° / V: 46.22° / D: 102.44° (QNO-6020R) H: 52.54° / V: 28.86° / D: 61.14° (QNO-6030R)	H: 109.7° (Wide) ~ 26.0° (Tele) / V: 60.8° (Wide) ~ 15.2° (Tele) / D: 131.3° (Wide) ~ 30.1° (Tele)	H: 111.0° / V: 63.0° / D: 128.0° (QND-7010R) H: 81.0° / V: 45.0° / D: 95.0° (QND-7020R) H: 53.0° / V: 31.0° / D: 62.0° (QND-7030R)	H: 103.8° (Wide) ~ 32.4° (Tele) / V: 53.7° (Wide) ~ 18.4° (Tele) / D: 121.9° (Wide) ~ 37.1° (Tele)	H: 111.0° / V: 63.0° / D: 133.0° (QND-6010R) H: 86.48° / V: 46.22° / D: 102.44° (QND-6020R) H: 52.54° / V: 28.86° / D: 61.14° (QND-6030R)
Focus Control	Simple Focus (motorized V/F) / Manual	-	Manual	-	Simple Focus (motorized V/F) / Manual	-	Manual	-
IR Viewable Length	30m (98.43ft)	20m (65.62ft) (QNO-7010R), 25m (82.02ft) (QNO-7020R), 30m (98.43ft) (QNO-7030R)	30m (98.43ft)	20m (65.62ft) : QNO-6010R, 25m (82.02ft) : QNO-6020R, 30m (98.43ft) : QNO-6030R	20m (65.62ft)	20m (65.62ft)	20m (65.62ft)	20m (65.62ft)
Pan / Tilt / Rotate	-	-	-	-	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°
Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)
Digital Noise Reduction	SSNR	SSNR	SSNR	SSNR	SSNR	SSNR	SSNR	SSNR
Digital Image Stabilization	-	-	-	-	-	-	-	-
Intelligent Video Analytics	Motion Detection with Metadata, Tampering, Defocus Detection	Motion Detection with Metadata, Tampering, Defocus Detection	Motion Detection with Metadata, Tampering, Defocus Detection	Motion Detection with Metadata, Tampering, Defocus Detection	Motion Detection with Metadata, Tampering, Defocus Detection	Motion Detection with Metadata, Tampering, Defocus Detection	Motion Detection with Metadata, Tampering, Defocus Detection	Motion Detection with Metadata, Tampering, Defocus Detection
Protocol	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI
Alarm I/O	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1
Audio	Uni-Directional	Uni-Directional	Uni-Directional	Uni-Directional	Uni-Directional	Uni-Directional	Uni-Directional	Uni-Directional
Edge Storage	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS
Environment Protection	IP66, IK10	IP66, IK10	IP66, IK10	IP66, IK10	-	IK08	-	IK08
Operating Temperature	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)
Power	Max. 7.0W (12V DC) Max. 8.0W (PoE)	Max. 6.0W (12V DC) Max. 7.0W (PoE)	Max. 7.0W (12V DC) Max. 8.0W (PoE)	Max. 6.0W (12V DC) Max. 7.0W (PoE)	Max. 6.4W (12V DC) Max. 7.2W (PoE)	Max. 5.8W (12V DC) Max. 7.0W (PoE) (QND-7010R) Max. 5.43W (12V DC) Max. 6.5W (PoE) (QND-7020R/7030R)	Max. 5.5W (12V DC) Max. 6.7W (PoE)	Max. 5.8W (12V DC) Max. 7.0W (PoE) (QND-6010R) Max. 5.43W (12V DC) Max. 6.5W (PoE) (QND-6020R/6030R)
Dimensions (WxHxD) / Weight	Ø70.0 x 246.0mm (Ø2.76" x 9.69") (Without Sunshield) 750g (1.65 lb)	Ø70.0 x 246.0mm (Ø2.76" x 9.69") (Without Sunshield) 730g (1.61 lb)	Ø70.0 x 246.0mm (Ø2.76" x 9.69") (Without Sunshield) 730g (1.61 lb)	Ø70.0 x 246.0mm (Ø2.76" x 9.69") (Without Sunshield) 730g (1.61 lb)	Ø119.8 x 98.8mm (Ø4.72" x 3.89") 355g (0.78 lb)	Ø110.0 x 86.0mm (Ø4.33" x 3.39") 290g (0.64 lb)	Ø119.8 x 98.8mm (Ø4.72" x 3.89") 325g (0.72 lb)	Ø110.0 x 86.0mm (Ø4.33" x 3.39") 290g (0.64 lb)
Additional Features	Lens Distortion Correction, Hallway View, WiseStream	Lens Distortion Correction, Hallway View, WiseStream	Lens Distortion Correction, Hallway View, WiseStream	Lens Distortion Correction, Hallway View, WiseStream	Lens Distortion Correction, Hallway View, WiseStream	Lens Distortion Correction, Hallway View, WiseStream	Lens Distortion Correction, Hallway View, WiseStream	Lens Distortion Correction, Hallway View, WiseStream



WISENET Q
QNV-7080R



WISENET Q
QNV-7010R/7020R/7030R



WISENET Q
QNV-6070R



WISENET Q
QNV-6010R/6020R/6030R

	4MP	4MP	2MP	2MP
Resolution	4MP	4MP	2MP	2MP
Imaging Device	1/3" 4M CMOS	1/3" 4M CMOS	1/2.9" 2.19M CMOS	1/2.9" 2.19M CMOS
Video Compression Format	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG	H.265, H.264, MJPEG
Resolution / Max. Frame Rate	4M / 20fps, 2M / 30fps	4M / 20fps, 2M / 30fps	2M / 30fps	2M / 30fps
Streaming Capacity	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)
Max. User Access	6 (Unicast)	6 (Unicast)	6 (Unicast)	6 (Unicast)
Min. Illumination	Color 0.15 Lux B/W : 0 Lux (IR LED on)	Color : 0.5 Lux (QNV-7010R), 0.4 Lux (QNV-7020R), 0.3 Lux (QNV-7030R) B/W : 0 Lux (IR LED on)	Color 0.095 Lux B/W : 0 Lux (IR LED on)	Color : 0.15 Lux B/W : 0 Lux (IR LED on)
Video Output	-	-	-	-
Lens	2.8 ~ 12mm (4.3x) motorized V/F (F1.4)	2.8mm fixed (F2.0) (QNV-7010R) 3.6mm fixed (F2.2) (QNV-7020R) 6mm fixed (F2.2) (QNV-7030R)	2.8 ~ 12mm (4.3x) Manual V/F (F1.4)	2.8mm fixed (F1.8) (QNV-6010R) 3.6mm fixed (F1.8) (QNV-6020R) 6mm fixed (F1.8) (QNV-6030R)
Angular Field of View	H : 109.7°(Wide) ~ 26.0°(Tele) / V : 60.8°(Wide) ~ 15.2°(Tele) / D : 131.3°(Wide) ~ 30.1°(Tele)	H : 110.0° / V : 63.0° / D : 133.0° (QNV-7010R) H : 81.0° / V : 45.0° / D : 95.0° (QNV-7020R) H : 53.0° / V : 31.0° / D : 62.0° (QNV-7030R)	H : 103.8°(Wide) ~ 32.4°(Tele) / V : 53.7°(Wide) ~ 18.4°(Tele) / D : 121.9°(Wide) ~ 37.1°(Tele)	H : 110.0° / V : 61.0° / D : 125.0° (QNV-6010R) H : 86.48° / V : 46.22° / D : 102.44° (QNV-6020R) H : 52.54° / V : 28.86° / D : 61.14° (QNV-6030R)
Focus Control	Simple Focus (motorized V/F) / Manual	-	Manual	-
IR Viewable Length	30m (98.43ft)	20m (65.62ft) (QNV-7010R), 25m (82.02ft) (QNV-7020R), 30m (98.43ft) (QNV-7030R)	30m (98.43ft)	20m (65.62ft) (QNV-6010R), 25m (82.02ft) (QNV-6020R), 30m (98.43ft) (QNV-6030R)
Pan / Tilt / Rotate	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°
Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)
Digital Noise Reduction	SSNR	SSNR	SSNR	SSNR
Digital Image Stabilization	-	-	-	-
Intelligent Video Analytics	Motion Detection with Metadata, Tampering, Defocus Detection	Motion Detection with Metadata, Tampering, Defocus Detection	Motion Detection with Metadata, Tampering, Defocus Detection	Motion Detection with Metadata, Tampering, Defocus Detection
Protocol	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI
Alarm I/O	1 / 1	1 / 1	1 / 1	1 / 1
Audio	Uni-Directional	Uni-Directional	Uni-Directional	Uni-Directional
Edge Storage	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS
Environment Protection	IP66, IK10	IP66, IK10	IP66, IK10	IP66, IK10
Operating Temperature	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)
Power	Max. 6.4W(12V DC) Max. 7.2W (PoE)	Max. 5.8W (12V DC), Max. 7.0W (PoE) (QNV-7010R) Max. 5.7W (12V DC), Max. 6.8W (PoE) (QNV-7020R/7030R)	Max. 5.5W (12V DC) Max. 6.7W (PoE)	Max. 5.8W (12V DC), Max. 7.0W (PoE) (QNV-6010R) Max. 5.7W (12V DC), Max. 6.8W (PoE) (QNV-6020R/6030R)
Dimensions (WxHxD) / Weight	Ø137.0 x 106.1mm (Ø5.39" x 4.18") 680g (1.5 lb)	Ø120.3 x 91.7mm (Ø4.74" x 3.61") 490g (1.08 lb)	Ø137.0 x 106.1mm (Ø5.39" x 4.18") 660g (1.46 lb)	Ø120.3 x 91.7mm (Ø4.74" x 3.61") 490g (1.08 lb)
Additional Features	Lens Distortion Correction, Hallway View, WiseStream	Lens Distortion Correction, Hallway View, WiseStream	Lens Distortion Correction, Hallway View, WiseStream	Lens Distortion Correction, Hallway View, WiseStream



WISENET P
PRN-4011



WISENET X
XRN-3010



WISENET X
XRN-2011



WISENET X
XRN-2010



WISENET X
XRN-1610S

	Linux	Linux	Linux	Linux	Linux
OS	Linux	Linux	Linux	Linux	Linux
Supported Compression	H.265, H.264, MJPEG, WiseStream	H.265, H.264, MJPEG, WiseStream	H.265, H.264, MJPEG, WiseStream	H.265, H.264, MJPEG, WiseStream	H.265, H.264, MJPEG, WiseStream
Max. Recording Bit Rate	400Mbps	300Mbps	256Mbps (H.265 4MP 32Cameras Real-Time Recording) 100Mbps (RAID 5 mode)	256Mbps (H.265 4MP 32Cameras Real-Time Recording)	180Mbps
Max # of Cameras	64	64	32	32	16
Internal Storage	Up to 12 SATA (Max. 96TB)	Up to 8 SATA (Max. 48TB)	Up to 8 SATA (Hot swap) Max. 48TB (Non RAID), Max.36TB (RAID 5)	Up to 8 SATA (Max. 48TB)	Up to 4 SATA (Max. 24TB)
External Storage	iSCSI	1 e-SATA	iSCSI	iSCSI, 1 e-SATA	iSCSI, 1 e-SATA
RAID	RAID 5/6	-	RAID 5	-	-
Hot Swap	Yes	-	Yes	-	-
Isolated Networks for Cameras / Source	Yes	Yes	Yes	Yes	Yes
Network Viewer Software	SSM, WebViewer, SmartViewer, iPOLiS Mobile	SSM, WebViewer, SmartViewer, iPOLiS Mobile	SSM, WebViewer, SmartViewer, iPOLiS Mobile	SSM, WebViewer, SmartViewer, iPOLiS Mobile	SSM, WebViewer, SmartViewer, iPOLiS Mobile
Local Monitor	HDMI (Up to 4K), VGA Support Dual Monitor: HDMI / VGA	HDMI (Up to 4K), VGA Support Dual Monitor: HDMI / VGA	HDMI (Up to 4K, 32CH Monitoring) Support Dual Monitor: HDMI / VGA	HDMI (Up to 4K, 32CH Monitoring) Support Dual Monitor: HDMI / VGA	HDMI (Up to 4K), VGA Support Dual Monitor: HDMI / VGA
Camera Support	Samsung, ONVIF	Samsung, ONVIF	Samsung, ONVIF	Samsung, ONVIF	Samsung, ONVIF
Features	<ul style="list-style-type: none"> • N+1 Failover Supported • ARB Redundancy Supported • WiseStream Support • Defocus Event Trigger 	<ul style="list-style-type: none"> • N+1 Failover Supported • ARB Redundancy Supported • WiseStream Support • Defocus Event Trigger 	<ul style="list-style-type: none"> • N+1 Failover Supported • ARB Redundancy Supported • WiseStream Support 	<ul style="list-style-type: none"> • N+1 Failover Supported • ARB Redundancy Supported • WiseStream Support 	<ul style="list-style-type: none"> • Plug & Play by 16 PoE / PoE+ Ports • WebViewer Supported • WiseStream Support • Defocus Event Trigger



WISENET X
XRN-1610



WISENET X
XRN-810S



WISENET X
XRN-410S



WISENET Q
QRN-810



WISENET Q
QRN-410

	Linux	Linux	Linux	Linux	Linux
OS	Linux	Linux	Linux	Linux	Linux
Supported Compression	H.265, H.264, MJPEG, WiseStream	H.265, H.264, MJPEG, WiseStream	H.265, H.264, MJPEG, WiseStream	H.265, H.264, MJPEG, WiseStream	H.265, H.264, MJPEG, WiseStream
Max. Recording Bit Rate	180Mbps	100Mbps	50Mbps	100Mbps	50Mbps
Max # of Cameras	16	8	4	8	4
Internal Storage	Up to 4 SATA (Max. 24TB)	Up to 2 SATA (Max. 12TB)	Up to 1 SATA (Max. 6TB)	Up to 1 SATA (Max. 6TB)	Up to 1 SATA (Max. 6TB)
External Storage	iSCSI, 1 e-SATA	-	-	-	-
RAID	-	-	-	-	-
Hot Swap	-	-	-	-	-
Isolated Networks for Cameras / Source	Yes	Yes	Yes	Yes	Yes
Network Viewer Software	SSM, WebViewer, SmartViewer, iPOLiS Mobile	SSM, WebViewer, SmartViewer, iPOLiS Mobile	SSM, WebViewer, SmartViewer, iPOLiS Mobile	SSM, WebViewer, SmartViewer, iPOLiS Mobile	SSM, WebViewer, SmartViewer, iPOLiS Mobile
Local Monitor	HDMI (Up to 4K), VGA Support Dual Monitor: HDMI / VGA	HDMI (Up to 4K), VGA	HDMI (Up to 4K), VGA	HDMI (Up to 4K), VGA	HDMI (Up to 4K), VGA
Camera Support	Samsung, ONVIF	Samsung, ONVIF	Samsung, ONVIF	Samsung, ONVIF	Samsung, ONVIF
Features	<ul style="list-style-type: none"> • WebViewer Supported • WiseStream Support • Defocus Event Trigger 	<ul style="list-style-type: none"> • Plug & Play by 8 PoE / PoE+ Ports • Defocus Event Trigger • ARB Supported • Easy Configuration (Setup Wizard, P2P (QR Code)) • Event Push to Smart Phone • Transmission Bandwidth 128Mbps • Defocus Event Trigger 	<ul style="list-style-type: none"> • Plug & Play by 4 PoE / PoE+ Ports • Defocus Event Trigger • ARB Supported • Easy Configuration (Setup Wizard, P2P (QR Code)) • Event Push to Smart Phone • Transmission Bandwidth 64Mbps • Defocus Event Trigger 	<ul style="list-style-type: none"> • Defocus Event Trigger • ARB Supported • Easy Configuration (Setup Wizard, P2P (QR Code)) • Event Push to Smart Phone • Transmission Bandwidth 128Mbps • Defocus Event Trigger 	<ul style="list-style-type: none"> • Defocus Event Trigger • ARB Supported • Easy Configuration (Setup Wizard, P2P (QR Code)) • Event Push to Smart Phone • Transmission Bandwidth 64Mbps • Defocus Event Trigger

NETWORK



SNB-8000

**WISENET III
SNB-7004**

**WISENET III
SNB-6011B**

**WISENET III
SNB-6010B**

**WISENET III
SNB-6005**

**WISENET III
SNB-6004**

**WISENET III
SNB-6003**

	5MP	3MP	2MP	2MP	2MP	2MP	2MP
Resolution	5MP	3MP	2MP	2MP	2MP	2MP	2MP
Imaging Device	1/1.8" 6M CMOS	1/2.8" 3.2M CMOS	1/2.8" 2.38M CMOS	1/2.8" 2.38M CMOS	1/1.9" 2.4M CMOS	1/2.8" 2.38M CMOS	1/2.8" 2.38M CMOS
Video Compression Format	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG
Resolution / Max. Frame Rate	5M / 20fps	3M / 30fps	2M / 30fps	2M / 30fps	2M / 60fps	2M / 60fps	2M / 60fps
Streaming Capacity	Multiple (Up to 6 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)
Max. User Access	10 (Unicast)	15 (Unicast)	15 (Unicast)	15 (Unicast)	15 (Unicast)	15 (Unicast)	15 (Unicast)
Min. Illumination	Color : 0.1 Lux B/W : 0.01 Lux	Color : 0.06 Lux B/W : 0.006 Lux	* Color : 0.3 Lux	* Color : 0.3 Lux	Color : 0.015 Lux B/W : 0.0015 Lux	Color : 0.03 Lux B/W : 0.002 Lux	Color : 0.03 Lux B/W : 0.03 Lux
Video Output	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type
Lens	-	-	2.4mm Pinhole (F 2.0)	4.6mm Pinhole (F 2.5)	-	-	-
Angular Field of View	-	-	H: 134.3° / V: 70.9°	H: 71° / V: 38°	-	-	-
Focus Control	Simple Focus / Manual	Simple Focus / Manual	-	-	Simple Focus / Manual	Simple Focus / Manual	Manual
IR Viewable Length	-	-	-	-	-	-	-
Pan / Tilt / Rotate	-	-	-	-	-	-	-
Day & Night	True (ICR)	True (ICR)	Electrical	Electrical	True (ICR)	True (ICR)	Electrical
Backlight Compensation	BLC	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)
Digital Noise Reduction	SSNR (2D+3D Noise Filter)	SSNR ^{III} (2D+3D Noise Filter)	SSNR ^{III} (2D+3D Noise Filter)	SSNR ^{III} (2D+3D Noise Filter)	SSNR ^{III} (2D+3D Noise Filter)	SSNR ^{III} (2D+3D Noise Filter)	SSNR ^{III} (2D+3D Noise Filter)
Digital Image Stabilization	-	Support	Support	Support	Support	Support	Support
Intelligent Video Analytics	Tampering, Audio Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection with Metadata	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection with Metadata	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection with Metadata	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection
Protocol	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform
Alarm I/O	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1
Audio	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional
Edge Storage	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS
Environment Protection	-	-	-	-	-	-	-
Operating Temperature	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)
Power	Max. 12.65W (24V AC) Max. 10.68W (12V DC) Max. 12.14W (PoE)	Max. 13.1W (24V AC) Max. 11.1W (12V DC) Max. 12.6W (PoE)	Max. 6.5W (12V DC) Max. 7.5W (PoE)	Max. 6.5W (12V DC) Max. 7.5W (PoE)	Max. 11.44W (24V AC) Max. 10.1W (12V DC) Max. 11.1W (PoE)	Max. 11.44W (24V AC) Max. 10.1W (12V DC) Max. 11.1W (PoE)	Max. 9.5W (24V AC) Max. 8.38W (12V DC) Max. 9.18W (PoE)
Dimensions (WxHxD) / Weight	73.1 x 66.6 x 147.0mm (2.88" x 2.62" x 5.79") 566g (1.25 lb)	73.1 x 66.6 x 147.8mm (2.88" x 2.62" x 5.82") 430g (0.95 lb)	Header : Ø24.0 x 50.0mm (Ø0.94" x 1.97"), 80g (0.18 lb) (Include 1.5m cable) Main unit : 131.1 x 28.0 x 86.0mm (5.16" x 1.1" x 3.39") 255g (0.56 lb)	Header : Ø24.0 x 42.4mm (Ø0.94" x 1.67"), 80g (0.18 lb) (Include 1.5m cable) Main unit : 131.1 x 28.0 x 86.0mm (5.16" x 1.1" x 3.39") 255g (0.56 lb)	73.1 x 66.6 x 147.8mm (2.88" x 2.62" x 5.82") 430g (0.95 lb)	73.1 x 66.6 x 147.8mm (2.88" x 2.62" x 5.82") 395g (0.87 lb)	73.1 x 66.6 x 136.2mm (2.88" x 2.62" x 5.36") 330g (0.73 lb)
Additional Features	P-Iris, RS-485	P-Iris, RS-485, Defog	Separated head and body, Defog	Separated head and body, Defog	P-Iris, RS-485, Defog	P-Iris, RS-485, Defog	P-Iris, RS-485, Defog

NETWORK



WISENET III
SNZ-6320



SNO-8081R



WISENET III
SNO-7084R



WISENET III
SNO-6084R



WISENET III
SNO-6011R



WISENET Lite
SNO-L6083R



WISENET Lite
SNO-L6013R

	2MP	5MP	3MP	2MP	2MP	2MP	2MP
Resolution	2MP	5MP	3MP	2MP	2MP	2MP	2MP
Imaging Device	1/2.8" 2.38M CMOS	1/1.8" 6M CMOS	1/2.8" 3.2M CMOS	1/2.8" 2.38M CMOS	1/2.8" 2.38M CMOS	1/2.9" 2.19M CMOS	1/2.9" 2.19M CMOS
Video Compression Format	H.264, MJPEG	H.265, H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG
Resolution / Max. Frame Rate	2M / 60fps	5M / 30fps	3M / 30fps	2M / 60fps	2M / 30fps	2M / 30fps	2M / 30fps
Streaming Capacity	Multiple (Up to 10 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)
Max. User Access	10 (Unicast)	10 (Unicast)	15 (Unicast)	15 (Unicast)	15 (Unicast)	6 (Unicast)	6 (Unicast)
Min. Illumination	Color: 0.15 Lux B/W: 0.015 Lux	Color: 0.12 Lux B/W: 0 Lux (IR LED on)	Color: 0.06 Lux B/W: 0 Lux (IR LED on)	Color: 0.03 Lux B/W: 0 Lux (IR LED on)	Color: 0.08 Lux B/W: 0 Lux (IR LED on)	Color: 0.095 Lux B/W: 0 Lux (IR LED on)	Color: 0.15 Lux B/W: 0 Lux (IR LED on)
VIDEO							
Video Output	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp	-	-
Lens	4.44 ~ 142.6mm (Optical 32x) F1.6(Wide) / F4.4(Tele)	3.93 ~ 9.4mm (2.4x) motorized V/F (F1.3)	3 ~ 8.5mm (2.8x) motorized V/F (F1.2)	3 ~ 8.5mm (2.8x) motorized V/F (F1.2)	3.8mm fixed (F2.0)	2.8 ~ 12mm (4.3x) V/F (F1.4)	3.6mm fixed (F1.8)
Angular Field of View	H: 62.8°(Wide) ~ 2.23°(Tele) / V: 36.8°(Wide) ~ 1.26°(Tele)	H: 93.4°(Wide) ~ 39.2°(Tele) / V: 68.1°(Wide) ~ 29.3°(Tele)	H: 100.12°(Wide) ~ 35.38°(Tele) / V: 73.76°(Wide) ~ 26.58°(Tele)	H: 105.5°(Wide) ~ 37.1°(Tele) / V: 57.5°(Wide) ~ 21.0°(Tele)	H: 84.5° / V: 45.8° / D: 98.8°	H: 103.8°(Wide) ~ 32.4°(Tele) / V: 53.7°(Wide) ~ 18.4°(Tele) / D: 121.9°(Wide) ~ 37.1°(Tele)	H: 86.5° / V: 47.8° / D: 101.2°
Focus Control	Auto / Manual / One push	Simple Focus (motorized V/F) / Manual	Simple Focus (motorized V/F) / Manual	Simple Focus (motorized V/F) / Manual	Manual	Manual	-
OPERATIONAL							
IR Viewable Length	-	30m (98.43ft)	30m (98.43ft)	30m (98.43ft)	15m (49.21ft)	20m (65.62ft)	20m (65.62ft)
Pan / Tilt / Rotate	-	-	-	-	-	-	-
Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB, 15fps)	BLC, DWDR	BLC, DWDR
Digital Noise Reduction	SSNRIII (2D+3D Noise Filter)	SSNR (2D+3D Noise Filter)	SSNRIII (2D+3D Noise Filter)	SSNRIII (2D+3D Noise Filter)	SSNRIII (2D+3D Noise Filter)	SSNR	SSNR
Digital Image Stabilization	Support	-	Support	Support	Support	-	-
Intelligent Video Analytics	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Motion Detection, Tampering, Audio Detection with Metadata	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Face Detection with Metadata	Motion Detection with Metadata, Tampering	Motion Detection with Metadata, Tampering
FEATURES							
Protocol	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI
Alarm I/O	1 / 1 (Relay)	1 / 1	1 / 1	1 / 1	1 / 0	-	-
Audio	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	-	Uni-Directional	Uni-Directional
Edge Storage	SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS, Local PC	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC	Micro SD/SDHC, NAS	Micro SD/SDHC, NAS
Environment Protection	-	IP66, IK10	IP66, IK10	IP66, IK10	IP66	IP66, IK10	IP66
Operating Temperature	-10°C ~ +55°C (+14°F ~ +131°F)	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-50°C ~ +55°C (-58°F ~ +131°F) (24V AC) -20°C ~ +55°C (-4°F ~ +131°F) (12V DC, PoE) * Start up above -10°C (+14°F)	-50°C ~ +55°C (-58°F ~ +131°F) (24V AC) -20°C ~ +55°C (-4°F ~ +131°F) (12V DC, PoE) * Start up above -10°C (+14°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)
Power	Max. 9.0W (12V DC) Max. 10.0W (PoE)	Max. 12.0W / 13.5W - Heater on (24V AC) Max. 10.0W / 11.5W - Heater on (12V DC) Max. 11.5W / 12.95W - Heater on (PoE)	Max. 13.0W / 19.0W - Heater on (24V AC) Max. 11.5W (12V DC) Max. 12.5W (PoE)	Max. 11.0W - Heater off Max. 17.0W - Heater on (24V AC)	Max. 8.5W (PoE)	Max. 5.9W (PoE)	Max. 5.7W (PoE)
Dimensions (WxHxD) / Weight	72.0 x 59.9 x 135.4mm (2.83" x 2.36" x 5.33") 540g (1.19 lb)	82.4 x 87.0 x 348.3mm (3.24" x 3.43" x 13.71") (Without Sunshield) 1.42Kg (3.13 lb)	82.4 x 82.4 x 312.6mm (3.24" x 3.24" x 12.31") (Without Sunshield) 1.19Kg (2.62 lb)	82.4 x 82.4 x 312.6mm (3.24" x 3.24" x 12.31") (Without Sunshield) 1.19Kg (2.62 lb)	77.1 x 83.0 x 302.4mm (3.04" x 3.27" x 11.91") 560g (1.23 lb)	Ø70.0 x 246.0mm (Ø2.76" x 9.69") (Without Sunshield) 700g (1.54 lb)	Ø58.6 x 165.2mm (Ø2.31" x 6.5") (Without Sunshield) 250g (0.55 lb)
Additional Features	RS-485, Defog	Lens Distortion Correction, Hallway View, P-Iris	P-Iris, Defog	P-Iris, Defog	Defog	Lens Distortion Correction, Hallway View	Lens Distortion Correction, Hallway View

NETWORK



SNF-8010/8010VM



**WISNET III
SND-7084**



**WISNET III
SND-6084**



**WISNET III
SND-6083**



**WISNET Lite
SND-L6013**



**WISNET Lite
SND-L6012**



**WISNET III
SND-7084R**



**WISNET III
SND-6084R**

	SNF-8010/8010VM	WISNET III SND-7084	WISNET III SND-6084	WISNET III SND-6083	WISNET Lite SND-L6013	WISNET Lite SND-L6012	WISNET III SND-7084R	WISNET III SND-6084R
Resolution	5MP	3MP	2MP	2MP	2MP	2MP	3MP	2MP
Imaging Device	1/1.8" 6M CMOS	1/2.8" 3.2M CMOS	1/2.8" 2.38M CMOS	1/2.8" 2.38M CMOS	1/2.9" 2.19M CMOS	1/2.9" 2.19M CMOS	1/2.8" 3.2M CMOS	1/2.8" 2.38M CMOS
Video Compression Format	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG
Resolution / Max. Frame Rate	5M / 20fps	3M / 30fps	2M / 60fps	2M / 60fps	2M / 30fps	2M / 30fps	3M / 30fps	2M / 60fps
Streaming Capacity	Multiple (Up to 5 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)
Max. User Access	10 (Unicast)	15 (Unicast)	15 (Unicast)	15 (Unicast)	6 (Unicast)	6 (Unicast)	15 (Unicast)	15 (Unicast)
Min. Illumination	Color: 0.2 Lux B/W: 0.02 Lux	Color: 0.06 Lux B/W: 0.006 Lux	Color: 0.03 Lux B/W: 0.002 Lux	Color: 0.03 Lux B/W: 0.03 Lux	Color: 0.15 Lux B/W: 0.15 Lux	Color: 0.15 Lux B/W: 0.15 Lux	Color: 0.06 Lux B/W: 0 Lux (IR LED on)	Color: 0.03 Lux B/W: 0 Lux (IR LED on)
Video Output	CVBS 1.0Vpp	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	-	-	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type
Lens	1.14mm fixed (F2.5)	3 ~ 8.5mm (2.8x) motorized V/F (F1.2)	3 ~ 8.5mm (2.8x) motorized V/F (F1.2)	3 ~ 8.5mm (2.8x) V/F (F1.2)	3.6mm fixed (F1.8)	2.8mm fixed (F1.8)	3 ~ 8.5mm (2.8x) motorized V/F (F1.2)	3 ~ 8.5mm (2.8x) motorized V/F (F1.2)
Angular Field of View	H: 187.0° / V: 187.0° / D: 187.0°	H: 100.12°(Wide) ~ 35.38°(Tele) / V: 73.76°(Wide) ~ 26.58°(Tele)	H: 105.5°(Wide) ~ 37.1°(Tele) / V: 57.5°(Wide) ~ 21.0°(Tele)	H: 106.18°(Wide) ~ 37.1°(Tele) / V: 58.42°(Wide) ~ 20.94°(Tele)	H: 86.5° / V: 47.8° / D: 101.2°	H: 110.0° / V: 61.0° / D: 125.0°	H: 100.12°(Wide) ~ 35.38°(Tele) / V: 73.76°(Wide) ~ 26.58°(Tele)	H: 105.5°(Wide) ~ 37.1°(Tele) / V: 57.5°(Wide) ~ 21.0°(Tele)
Focus Control	Manual	Simple Focus (motorized V/F) / Manual	Simple Focus (motorized V/F) / Manual	Manual	-	-	Simple Focus (motorized V/F) / Manual	Simple Focus (motorized V/F) / Manual
IR Viewable Length	-	-	-	-	-	-	25m (82.02ft)	15m (49.21ft)
Pan / Tilt / Rotate	-	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°
Day & Night	True (ICR)	True (ICR)	True (ICR)	Electrical	Electrical	Electrical	True (ICR)	True (ICR)
Backlight Compensation	WDR (60dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	BLC, DWDR	BLC, DWDR	WDR (120dB)	WDR (120dB)
Digital Noise Reduction	SSNRIII (2D+3D Noise Filter)	SSNRIII (2D+3D Noise Filter)	SSNRIII (2D+3D Noise Filter)	SSNRIII (2D+3D Noise Filter)	SSNR	SSNR	SSNRIII (2D+3D Noise Filter)	SSNRIII (2D+3D Noise Filter)
Digital Image Stabilization	-	Support	Support	Support	-	-	Support	Support
Intelligent Video Analytics	Motion Detection, Audio Detection, Tampering	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Motion Detection with Metadata, Tampering	Motion Detection with Metadata, Tampering	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection
Protocol	ONVIF Profile S, SUNAPI	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform
Alarm I/O	1 / 1	1 / 1	1 / 1	1 / 1	-	-	1 / 1	1 / 1
Audio	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Uni-Directional	Uni-Directional	Bi-Directional	Bi-Directional
Edge Storage	Micro SD/SDHC/SDXC, NAS IP66, IK10 / EN-61373/50155 (SNF-8010VM)	Micro SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS	Micro SD/SDHC, NAS	Micro SD/SDHC, NAS	Micro SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS
Environment Protection	-	-	-	-	-	-	-	-
Operating Temperature	-10°C ~ +55°C (+14°F ~ +131°F) (SNF-8010) -30°C ~ +55°C (-22°F ~ +131°F) * Start up above -25°C (-13°F) (SNF-8010VM)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)
Power	Max. 8.7W (12V DC) Max. 10.3W (PoE) mode A only (SNF-8010VM)	Max. 9.6W (12V DC) Max. 11.6W (PoE)	Max. 8.79W (12V DC) Max. 9.57W (PoE)	Max. 8.09W (12V DC) Max. 8.94W (PoE)	Max. 2.4W (PoE)	Max. 2.4W (PoE)	Max. 10.0W (12V DC) Max. 11.0W (PoE)	Max. 9.0W (12V DC, PoE)
Dimensions (WxHxD) / Weight	Ø145.9 x 49.6mm (Ø5.74" x 1.95") 780g (1.72 lb) (SNF-8010) Ø145.9 x 62.4mm (Ø5.74" x 2.46") 800g (1.76 lb) (SNF-8010VM)	Ø132.1 x 107.6mm (Ø5.2" x 4.24") 605g (1.33 lb)	Ø132.1 x 107.6mm (Ø5.2" x 4.24") 505g (1.11 lb)	Ø132.1 x 107.6mm (Ø5.2" x 4.24") 485g (1.07 lb)	Ø110.0 x 86.0mm (Ø4.33" x 3.39") 250g (0.55 lb)	Ø110.0 x 86.0mm (Ø4.33" x 3.39") 240g (0.53 lb)	Ø132.1 x 107.6mm (Ø5.2" x 4.24") 575g (1.27 lb)	Ø132.1 x 107.6mm (Ø5.2" x 4.24") 525g (1.16 lb)
Additional Features	Various Viewing Compositions, M12 Connector (SNF-8010VM)	P-Iris, Defog	P-Iris, Defog	Defog	Lens Distortion Correction, Hallway View	Lens Distortion Correction, Hallway View	P-Iris, Defog	P-Iris, Defog



WISENET III
SND-6011R



WISENET Lite
SND-L6083R



WISENET Lite
SND-L6013R



SNV-8080



WISENET III
SNV-7084



WISENET III
SNV-6084



WISENET III
SNV-6013



WISENET III
SNV-6012M

	2MP	2MP	2MP	5MP	3MP	2MP	2MP	2MP
Resolution	2MP	2MP	2MP	5MP	3MP	2MP	2MP	2MP
Imaging Device	1/2.8" 2.38M CMOS	1/2.9" 2.19M CMOS	1/2.9" 2.19M CMOS	1/1.8" 6M CMOS	1/2.8" 3.2M CMOS	1/2.8" 2.38M CMOS	1/2.8" 2.38M CMOS	1/2.8" 2.38M CMOS
Video Compression Format	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG
Resolution / Max. Frame Rate	2M / 30fps	2M / 30fps	2M / 30fps	5M / 20fps	3M / 30fps	2M / 60fps	2M / 60fps	2M / 60fps
Streaming Capacity	Multiple (Up to 10 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 6 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)
Max. User Access	15 (Unicast)	6 (Unicast)	6 (Unicast)	10 (Unicast)	15 (Unicast)	15 (Unicast)	15 (Unicast)	15 (Unicast)
Min. Illumination	Color : 0.08 Lux B/W : 0 Lux (IR LED on)	Color : 0.095 Lux B/W : 0 Lux (IR LED on)	Color : 0.15 Lux B/W : 0 Lux (IR LED on)	Color : 0.1 Lux B/W : 0.01 Lux	Color : 0.06 Lux B/W : 0.006 Lux	Color : 0.03 Lux B/W : 0.002 Lux	Color : 0.15 Lux B/W : 0.015 Lux	Color : 0.15 Lux B/W : 0.015 Lux
Video Output	CVBS 1.0Vpp	-	-	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type
Lens	3.8mm fixed (F2.0)	2.8 ~ 12mm (4.3x) V/F (F1.4)	3.6mm fixed (F1.8)	3.6 ~ 9.4mm (2.6x) motorized V/F (F1.2)	3 ~ 8.5mm (2.8x) motorized V/F (F1.2)	3 ~ 8.5mm (2.8x) motorized V/F (F1.2)	2.8mm fixed (F1.8)	3mm fixed (F2.0)
Angular Field of View	H : 84.5° / V : 45.8° / D : 98.8°	H : 103.8°(Wide) ~ 32.4°(Tele) / V : 53.7°(Wide) ~ 18.4°(Tele) / D : 121.9°(Wide) ~ 37.1°(Tele)	H : 86.5° / V : 47.8° / D : 101.2°	H : 104.0°(Wide) ~ 39.2°(Tele) / V : 75.2°(Wide) ~ 29.3°(Tele)	H : 100.12°(Wide) ~ 35.38°(Tele) / V : 73.76°(Wide) ~ 26.58°(Tele)	H : 105.5°(Wide) ~ 37.1°(Tele) / V : 57.5°(Wide) ~ 21.0°(Tele)	H : 112.0° / V : 62.0°	H : 103.1° / V : 53.9° / D : 124.5°
Focus Control	-	Manual	-	Simple Focus / Manual	Simple Focus (motorized V/F) / Manual	Simple Focus (motorized V/F) / Manual	-	-
IR Viewable Length	10m (32.81ft)	15m (49.21ft)	15m (49.21ft)	-	-	-	-	-
Pan / Tilt / Rotate	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	-	-10° ~ 10° / 0° ~ 90° / -
Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	Electrical	Electrical
Backlight Compensation	WDR (120dB)	BLC, DWDR	BLC, DWDR	BLC	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)
Digital Noise Reduction	SSNR ^{III} (2D+3D Noise Filter)	SSNR	SSNR	SSNR (2D+3D Noise Filter)	SSNR ^{III} (2D+3D Noise Filter)	SSNR ^{III} (2D+3D Noise Filter)	SSNR ^{III} (2D+3D Noise Filter)	SSNR ^{III} (2D+3D Noise Filter)
Digital Image Stabilization	Support	-	-	-	Support	Support	Support	Support
Intelligent Video Analytics	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Motion Detection with Metadata, Tampering	Motion Detection with Metadata, Tampering	Motion Detection, Tampering, Audio Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Face Detection, People counting, Zone analyzing	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Face Detection
Protocol	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S & G, SUNAPI	ONVIF Profile S & G, SUNAPI	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform
Alarm I/O	1 / 0	-	-	1 / 1	1 / 1	1 / 1	-	-
Audio	-	Uni-Directional	Uni-Directional	Bi-Directional	Bi-Directional	Bi-Directional	-	-
Edge Storage	Micro SD/SDHC/SDXC	Micro SD/SDHC, NAS	Micro SD/SDHC, NAS	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS
Environment Protection	-	-	-	IP66, IK10	IP66, IK10	IP66, IK10	IP66, IK10	IP66, IK10 / EN50155, EN50121
Operating Temperature	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-30°C ~ +55°C (-22°F ~ +131°F)
Power	Max. 8.0W (PoE)	Max. 5.4W (PoE)	Max. 5.9W (PoE)	Max. 14.2W (24V AC) Max. 11.5W (12V DC) Max. 12.95W (PoE)	Max. 11.0W / 13.0W - Heater on (24V AC) Max. 9.0W / 11.5W - Heater on (12V DC) Max. 10.0W / 12.5W - Heater on (PoE)	Max. 14.0W - Heater on (24V AC, 12V DC) Max. 12.95W - Heater on (PoE)	Max. 7.5W (PoE)	Max. 7.5W (PoE)
Dimensions (WxHxD) / Weight	Ø120.0 x 101.8mm (Ø4.72" x 4.01") 380g (0.84 lb)	Ø119.8 x 98.8mm (Ø4.72" x 3.89") 290g (0.64 lb)	Ø110.0 x 86.0mm (Ø4.33" x 3.39") 245g (0.54 lb)	Ø160.0 x 118.5mm (Ø6.3" x 4.67") 980g (2.16 lb)	Ø160.0 x 118.5mm (Ø6.3" x 4.67") 960g (2.12 lb)	Ø160.0 x 118.5mm (Ø6.3" x 4.67") 985g (2.17 lb)	Ø112.8 x 63.7mm (Ø4.44" x 2.51") 550g (1.21 lb)	135.2 x 54.3 x 124.5mm (5.32" x 2.14" x 4.9") 530g (1.17 lb)
Additional Features	Defog	Lens Distortion Correction, Hallway View	Lens Distortion Correction, Hallway View	-	P-Iris, Defog	P-Iris, Defog	Defog	Defog, M12 connector

NETWORK



SNV-8081R



**WISENET III
SNV-7084R**



**WISENET III
SNV-6085R**



**WISENET III
SNV-6084R**



**WISENET Lite
SNV-L6083R**



**WISENET Lite
SNV-L6013R**



**WISENET Lite
SNV-L6014RM/L6014RBM**

	SNV-8081R	SNV-7084R	SNV-6085R	SNV-6084R	SNV-L6083R	SNV-L6013R	SNV-L6014RM/L6014RBM
Resolution	5MP	3MP	2MP	2MP	2MP	2MP	2MP
Imaging Device	1/1.8" 6M CMOS	1/2.8" 3.2M CMOS	1/2.8" 2.38M CMOS	1/2.8" 2.38M CMOS	1/2.9" 2.19M CMOS	1/2.9" 2.19M CMOS	1/2.9" 2.19M CMOS
Video Compression Format	H.265, H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG
Resolution / Max. Frame Rate	5M / 30fps	3M / 30fps	2M / 60fps	2M / 60fps	2M / 30fps	2M / 30fps	2M / 30fps
Streaming Capacity	Multiple (Up to 3 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)	Multiple (Up to 3 Profiles)
Max. User Access	10 (Unicast)	15 (Unicast)	15 (Unicast)	15 (Unicast)	6 (Unicast)	6 (Unicast)	6 (Unicast)
Min. Illumination	Color: 0.15 Lux B/W: 0 Lux (IR LED on)	Color: 0.06 Lux B/W: 0 Lux (IR LED on)	Color: 0.09 Lux B/W: 0 Lux (IR LED on)	Color: 0.03 Lux B/W: 0 Lux (IR LED on)	Color: 0.095 Lux B/W: 0 Lux (IR LED on)	Color: 0.15 Lux B/W: 0 Lux (IR LED on)	Color: 0.15 Lux B/W: 0 Lux (IR LED on)
VIDEO							
Video Output	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	CVBS 1.0Vpp DIP Connector Type	-	-	-
Lens	3.93 ~ 9.4mm (2.4x) motorized V/F (F1.3)	3 ~ 8.5mm (2.8x) motorized V/F (F1.2)	10 ~ 23mm (2.3x) motorized V/F (F1.6)	3 ~ 8.5mm (2.8x) motorized V/F (F1.2)	2.8 ~ 12mm (4.3x) V/F (F1.4)	3.6mm fixed (F1.8)	3.6mm fixed (F1.8)
Angular Field of View	H: 93.4°(Wide) ~ 39.2°(Tele) / V: 68.1°(Wide) ~ 29.3°(Tele)	H: 100.12°(Wide) ~ 35.38°(Tele) / V: 73.76°(Wide) ~ 26.58°(Tele)	H: 31.3°(Wide) ~ 13.9°(Tele) / V: 17.1°(Wide) ~ 7.8°(Tele)	H: 105.5°(Wide) ~ 37.1°(Tele) / V: 57.5°(Wide) ~ 21.0°(Tele)	H: 103.8°(Wide) ~ 32.4°(Tele) / V: 53.7°(Wide) ~ 18.4°(Tele) / D: 121.9°(Wide) ~ 37.1°(Tele)	H: 86.5° / V: 47.8° / D: 101.2°	H: 86.5° / V: 47.8° / D: 101.2°
Focus Control	Simple Focus (motorized V/F) / Manual	Simple Focus (motorized V/F) / Manual	Simple Focus (motorized V/F) / Manual	Simple Focus (motorized V/F) / Manual	Manual	-	-
OPERATIONAL							
IR Viewable Length	30m (98.43ft)	25m (82.02ft)	20m (65.62ft)	15m (49.21ft)	20m (65.62ft)	15m (49.21ft)	15m (49.21ft)
Pan / Tilt / Rotate	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 354° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	-5° ~ 5° / 0° ~ 67° / 90°	-5° ~ 5° / 0° ~ 67° / 90°
Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	BLC, DWDR	BLC, DWDR	BLC, DWDR
Digital Noise Reduction	SSNR (2D+3D Noise Filter)	SSNR III (2D+3D Noise Filter)	SSNR III (2D+3D Noise Filter)	SSNR III (2D+3D Noise Filter)	SSNR	SSNR	SSNR
Digital Image Stabilization	Support	Support	Support	Support	-	-	-
Intelligent Video Analytics	Motion Detection, Tampering, Audio Detection with Metadata	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Motion Detection with Metadata, Tampering	Motion Detection with Metadata, Tampering	Motion Detection with Metadata, Tampering
FEATURES							
Protocol	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S & G, SUNAPI	ONVIF Profile S, SUNAPI	ONVIF Profile S, SUNAPI
Alarm I/O	1 / 1	1 / 1	1 / 1	1 / 1	-	-	-
Audio	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Uni-Directional	Uni-Directional	Uni-Directional
Edge Storage	SD/SDHC/SDXC, NAS, Local PC	Micro SD/SDHC/SDXC, NAS	Micro SD/SDHC, NAS, Local PC	SD/SDHC/SDXC, NAS	Micro SD/SDHC, NAS	Micro SD/SDHC, NAS	Micro SD/SDHC, NAS
Environment Protection	IP66, IK10	IP66, IK10	IP66, IK10	IP66, IK10	IP66, IK10	IP66, IK10	IP66, IK10
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-40°C ~ +55°C (-40°F ~ +131°F) (24V AC) -20°C ~ +55°C (-4°F ~ +131°F) (12V DC, PoE) * Start up above -10°C (+14°F)	-40°C ~ +55°C (-40°F ~ +131°F) * Start up above -35°C (-31°F)	-40°C ~ +55°C (-40°F ~ +131°F) (24V AC) -20°C ~ +55°C (-4°F ~ +131°F) (12V DC, PoE) * Start up above -10°C (+14°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -20°C (-4°F)
Power	Max. 12.0W / 13.5W - Heater on (24V AC) Max. 10.0W / 11.5W - Heater on (12V DC) Max. 11.5W / 12.95W - Heater on (PoE)	Max. 12.0W / 15.0W - Heater on (24V AC) Max. 10.5W (12V DC) Max. 11.5W (PoE)	Max. 11.0W - Heater off Max. 12.95W - Heater on (24V AC, 12V DC, PoE)	Max. 9.5W / Max. 13.5W - Heater on (24V AC)	Max. 5.8W (PoE)	PoE	PoE
Dimensions (WxHxD) / Weight	Ø160.0 x 118.5mm (Ø6.3" x 4.67") 955g (2.11 lb)	Ø160.0 x 118.5mm (Ø6.3" x 4.67") 975g (2.15 lb)	Ø160.0 x 118.5mm (Ø6.3" x 4.67") 970g (2.14 lb)	Ø160.0 x 118.5mm (Ø6.3" x 4.67") 960g (2.12 lb)	Ø137.0 x 106.1mm (Ø5.39" x 4.18") 670g (1.48 lb)	99.0 x 52.0 x 100.0mm (3.9" x 2.05" x 3.94") 300g (0.66 lb)	99.0 x 52.0 x 100.0mm (3.9" x 2.05" x 3.94") 300g (0.66 lb)
Additional Features	Lens Distortion Correction, Hallway View, P-Iris	P-Iris, Defog	P-Iris, Defog	P-Iris, Defog	Lens Distortion Correction, Hallway View	Lens Distortion Correction, Hallway View	M12 connector, Lens Distortion Correction, Hallway View, Built-in mic



**WISENET III
SNP-6321H**



**WISENET III
SNP-6321**



**WISENET III plus
SNP-6320H**



**WISENET III plus
SNP-6320**



**WISENET Lite
SNP-L6233H/L6233**



**WISENET III plus
SNP-6320RH**



**WISENET Lite
SNP-L6233RH**

	2MP	2MP	2MP	2MP	2MP	2MP	2MP
Resolution	2MP	2MP	2MP	2MP	2MP	2MP	2MP
Imaging Device	1/2.8" 2.38M CMOS	1/2.8" 2.38M CMOS	1/2.8" 2.38M CMOS	1/2.8" 2.38M CMOS	1/2.8" 2.38M CMOS	1/2.8" 2.38M CMOS	1/2.8" 2.38M CMOS
Video Compression Format	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG	H.264, MJPEG
Resolution / Max. Frame Rate	2M / 60fps	2M / 60fps	2M / 60fps	2M / 60fps	2M / 30fps	2M / 60fps	2M / 30fps
Streaming Capacity	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)	Multiple (Up to 10 Profiles)
Max. User Access	10 (Unicast)	10 (Unicast)	15 (Unicast)	15 (Unicast)	10 (Unicast)	15 (Unicast)	15 (Unicast)
Min. Illumination	Color: 0.15 Lux B/W: 0.015 Lux	Color: 0.15 Lux B/W: 0.015 Lux	Color: 0.2 Lux B/W: 0.01 Lux	Color: 0.2 Lux B/W: 0.01 Lux	Color: 0.15 Lux B/W: 0.015 Lux	Color: 0.1 Lux B/W: 0 Lux (IR LED on)	Color: 0.1 Lux B/W: 0 Lux (IR LED on)
Video Output	CVBS 1.0Vpp	CVBS 1.0Vpp	CVBS 1.0Vpp	CVBS 1.0Vpp	CVBS 1.0Vpp	CVBS 1.0Vpp	CVBS 1.0Vpp
Lens	4.44 ~ 142.6mm (Optical 32x) F1.6(Wide) / F4.4(Tele)	4.44 ~ 142.6mm (Optical 32x) F1.6(Wide) / F4.4(Tele)	4.44 ~ 142.6mm (Optical 32x) F1.6(Wide) / F4.4(Tele)	4.44 ~ 142.6mm (Optical 32x) F1.6(Wide) / F4.4(Tele)	4.44 ~ 102.1mm (Optical 23x)	4.4 ~ 140.8mm (IR Corrected Optical 32x) F1.6(Wide) / F4.9(Tele)	4.4 ~ 101.2mm (IR Corrected Optical 23x) F1.6(Wide) / F4.5(Tele)
Angular Field of View	H: 62.8°(Wide) ~ 2.23°(Tele) / V: 36.8°(Wide) ~ 1.26°(Tele)	H: 62.8°(Wide) ~ 2.23°(Tele) / V: 36.8°(Wide) ~ 1.26°(Tele)	H: 62.8°(Wide) ~ 2.23°(Tele) / V: 36.8°(Wide) ~ 1.26°(Tele)	H: 62.8°(Wide) ~ 2.23°(Tele) / V: 36.8°(Wide) ~ 1.26°(Tele)	H: 62.8°(Wide) ~ 3.14°(Tele) / V: 36.8°(Wide) ~ 1.76°(Tele)	H: 63.68°(Wide) ~ 2.24°(Tele) / V: 37.52°(Wide) ~ 1.28°(Tele)	H: 63.68°(Wide) ~ 3.1°(Tele) / V: 37.52°(Wide) ~ 1.76°(Tele)
Focus Control	Auto / Manual / One push	Auto / Manual / One push	Auto / Manual / One push	Auto / Manual / One push	Auto / Manual / One push	AF / One-shot AF / Manual	AF / One-shot AF / Manual
IR Viewable Length	-	-	-	-	-	150m (492.13ft)	100m (328.08ft)
Pan / Tilt / Rotate	360° Endless / 210° (-15° ~ 195°) / -	360° Endless / 210° (-15° ~ 195°) / -	360° Endless / 210° (-15° ~ 195°) / -	360° Endless / 210° (-15° ~ 195°) / -	360° Endless / 210° (-15° ~ 195°) / -	360° Endless / 190° (-5° ~ 185°) / -	360° Endless / 190° (-5° ~ 185°) / -
Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (100dB)	WDR (120dB)	WDR (100dB)
Digital Noise Reduction	SSNRIII (2D+3D Noise Filter)	SSNRIII (2D+3D Noise Filter)	SSNRIII (2D+3D Noise Filter)	SSNRIII (2D+3D Noise Filter)	SSNRIII (2D+3D Noise Filter)	SSNRIII (2D+3D Noise Filter)	SSNR
Digital Image Stabilization	Support	Support	Support	Support	Support	Support	Support
Intelligent Video Analytics	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection	Tampering, Virtual Line, Enter / Exit, (Dis)Appear, Audio Detection, Face Detection
Protocol	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI, Open Platform	ONVIF Profile S, SUNAPI
Alarm I/O	4 / 2 (Relay)	4 / 2 (Relay)	4 / 2 (Relay)	4 / 2 (Relay)	4 / 2 (Relay)	4 / 3 (Relay)	4 / 3 (Relay)
Audio	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional	Bi-Directional
Edge Storage	SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS	Micro SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS	SD/SDHC/SDXC, NAS, Local PC	SD/SDHC/SDXC, NAS, Local PC
Environment Protection	IP66, IK10	IK10 (With SHP-3701H)	IP66, IK10	IK10 (With SHP-3701H)	IP66, IK10 (SNP-L6233H) IK10 (With SHP-3701H) (SNP-L6233)	IP66, IK10	IP66, IK10
Operating Temperature	-50°C ~ +55°C (-58°F ~ +131°F) (24V AC) -30°C ~ +55°C (-22°F ~ +131°F) (PoE+)	-10°C ~ +55°C (+14°F ~ +131°F)	-50°C ~ +55°C (-58°F ~ +131°F) (24V AC) -30°C ~ +55°C (-22°F ~ +131°F) (PoE+)	-10°C ~ +55°C (+14°F ~ +131°F)	-50°C ~ +55°C (-58°F ~ +131°F) (24V AC) -30°C ~ +55°C (-22°F ~ +131°F) (PoE+) (SNP-L6233H) -10°C ~ +55°C (+14°F ~ +131°F) (SNP-L6233)	-50°C ~ +55°C (-58°F ~ +131°F)	-50°C ~ +55°C (-58°F ~ +131°F)
Power	Max. 65.0W - AC & PoE Heater on (24V AC) Max. 25.0W - 24V AC Heater off / PoE Heater on (PoE+)	Max. 20.0W (24V AC, PoE+)	Max. 24.0W (24V AC, PoE+) Max. 65.0W - Heater on (24V AC)	Max. 20.0W (24V AC, PoE+)	Max. 65.0W - AC & PoE Heater on (24V AC) Max. 25.0W - PoE Heater on (PoE+) (SNP-L6233H) Max. 20.0W (24V AC, PoE+) (SNP-L6233)	Max. 30.0W - Heater off Max. 35.0W / 90.0W - Heater off / on, IR on (24V AC)	Max. 30.0W - Heater off Max. 35.0W / 90.0W - Heater off / on, IR on (24V AC)
Dimensions (WxHxD) / Weight	Ø223.4 x 293.6mm (Ø8.8" x 11.56") 3.2Kg (7.05 lb)	Ø152.0 x 218.0mm (Ø5.98" x 8.58") 1.8Kg (3.97 lb)	Ø223.4 x 293.6mm (Ø8.8" x 11.56") 3.3Kg (7.28 lb)	Ø152.0 x 218.0mm (Ø5.98" x 8.58") 2.2Kg (4.85 lb)	Ø223.4 x 293.6mm (Ø8.8" x 11.56") 3.2Kg (7.05 lb) (SNP-L6233H) Ø152.0 x 218.0mm (Ø5.98" x 8.58") 1.8Kg (3.97 lb) (SNP-L6233)	Ø248.0 x 399.5mm (Ø9.76" x 15.73") 7.1Kg (15.65 lb)	Ø248.0 x 399.5mm (Ø9.76" x 15.73") 7.1Kg (15.65 lb)
Additional Features	RS-485, Defog	RS-485, Defog	Auto tracking, RS-485, Defog	Auto tracking, RS-485, Defog	RS-485, Defog	Auto tracking, RS-485/422, Defog	RS-485/422, Defog

NETWORK

NVR



SRM-872

OS	Linux
Supported Compression	H.264, MJPEG
Max. Recording Bit Rate	64Mbps
Max # of Cameras	8
Internal Storage	Up to 1 SATA (2.5")
External Storage	-
RAID	-
Hot Swap	Yes
Isolated Networks for Cameras / Source	Yes
Network Viewer Software	SmartViewer AUTO, iPOLIS Mobile AUTO
Local Monitor	HDMI / VGA
Camera Support	Samsung, ONVIF
Features	<ul style="list-style-type: none"> • Plug & Play by 8 PoE Ports • GPS Supported • Standards Approval for Transportation (EN50155, EN61373)

Encoder / Decoder



SPE-400



SPE-101



SPE-100

	SPE-400	SPE-101	SPE-100
Max. # of Cameras	4	1	1
Supported Compression	H.264, MJPEG, MPEG-4	H.264, MJPEG, MPEG-4	H.264, MJPEG, MPEG-4
Max. Resolution	704 x 480 / 704 x 576 (NTSC / PAL)	704 x 480 / 704 x 576 (NTSC / PAL)	704 x 480 / 704 x 576 (NTSC / PAL)
Max. Frame Rate per Channe	30/25fps (NTSC / PAL)	30/25fps (NTSC / PAL)	30/25fps (NTSC / PAL)
Bi-Directional Audio	Yes	-	Yes
RS-485	4	1	1
Alarm I/O	4 / 4	-	1 / 1
SD Card	SD/SDHC	-	SD/SDHC
ONVIF	Yes	Yes	Yes
Power	12VDC	12VDC / PoE	12VDC / PoE

iSCSI External Storage




SRB-1605

OS	Linux
Max. recording bandwidth	800Mbps
Internal HDD	Max.16 Hot swappable HDDs (Max. 128TB) * RAID 0 mode
RAID	0 / 10 / 5 / 6, RAID5 + Hotstandby
iSCSI volume	Max. 8 NVRs can be connected
Setup	One-Touch Setup of RAID volume Setup via webpage & remote storage management S/W
Redundancy	Network failover, Load balancing
Mechanical	4 Gigabit Ethernet Ports 3U chassis with Front Key-Lock
Features	Dual SMPS for high reliability



SPD-400



SPD-150

	SPD-400	SPD-150
Video Out	HDMI, VGA, CVBS	HDMI, VGA, CVBS
Resolution	H.264 : up to 2M / Quad View-up to 720p	HDMI up to 4K, VGA up to 1080p
Display	Single View, Quad View	(HDMI) 1 / 4 / 6 / 8 / 9 / 13 / 16 / 25 / 36(32) / 2V / 3V (VGA) 1 / 4 / 6 / 8 / 9 / 13 / 16 Split Mode, Hallway View Mode (Up to 20 Layouts and Sequence)
Support Device	Samsung, Axis	Wisenet
WebViewer	Supported OS : Window XP Supported Browser : IE 7.0 or 8.0, Firefox 2.x, 3.x, Chrome, Safari	-
Power	12V DC	12V DC, PoE
Additional Features	-	Up to 48CH, H.265 / H.264 / MJPEG Codec, Layout Sequence Support

Wisenet SSM

Wisenet SSM is video management software with features for both traditional and contemporary surveillance operations. It mainly consists of two parts; server and client software giving users a simple and easy to expand architecture. Server software includes core server for system management, plugins for intelligent business reports, transaction server to link your system to other surveillance areas such as access control, video decoder for wall display, and more. On the other hand, client software provides PC console for operators in security room and mobile viewer for guards on the move.

What's New in Wisenet SSM



Free Trial License

Users are given 45 days of trial period before activating license. During this period full features including recording are available. After trial periods, features will be limited and SSM will generate a warning message.




Single Core Server with Clustering

Basic servers such as MG, RS, SM, HA have been put in a single "Core Server" for new launched Wisenet SSM. In addition, these "Core Servers" can be clustered together providing higher level of reliability. From Wisenet SSM, a group of clustered core servers will be named 'Domain' and in the same domain, core servers will synchronize data.




New Client User Interface


You can play back recorded video during live streaming and easily control playback up to 32x as well as reverse playback. Also Wisenet SSM displays the events in the same area as thumbnails making it easier to carry out a detailed search.



Live Streaming




Display Events as Thumbnails



Location of Events for Google Map

System configuration



General	Wisenet SSM (v2.0)
System	
Maximum Number of Monitoring Channel	Up to 10,000channel / domain
Maximum Number of Recording Channel	Up to 10,000channel / domain
Architecture	Server / Client
Clients	Console Client, Mobile Viewer
Supported Devices	Network camera / encoder / decoder, DVR / NVR, Controller
Basic Component	
Core Server	<ul style="list-style-type: none"> Centralized License Management: 45 days free trial Server Clustering: Data sharing, Failure management System Dashboard: Real-time system status monitoring User Management: Device access authority, Feature level authority Federation: Multi-tier domain federation, Max 100 domains Centralized Device Configuration: Auto / Manual Device and add-on server registration Device Connection: Up to 3,000 channel Event Configuration: 4 levels event priority, Configurable event color Event Action: Rule based event and triggering action setup Layout & Pattern: User defined layout and tile pattern
Console Client	<ul style="list-style-type: none"> Tab Based Window: Live, Advanced search, Event, Configuration, Retail Number of Channels: Max 100 channels, Max 64 channels per tab Decoding: Hardware accelerator supported (NVIDIA CUDA) Playback: Multi channel playback, Bookmark Real-time Event: Event filtering by status, type, and priority Event Search: Event acknowledgement history Smart Search: Search by virtual area and virtual line Video Summary: Image preview, Video summary history management POS Text Search: Receipt list area, Keyword search Heatmap: Search by object type (Person, Vehicle) and time Counting Analysis: Statistic view, Map view, Report by date



WISENET HD+
HCB-6001



WISENET HD+
HCB-6000



WISENET HD+
HCO-6080R



WISENET HD+
HCO-6070R



WISENET HD+
HCD-6080R



WISENET HD+
HCD-6070R

TV Lines / Resolutions	2MP	2MP	2MP	2MP	2MP	2MP
VIDEO						
Imaging Device	1/2.8" 2M CMOS	1/2.9" 2M CMOS	1/2.9" 2M CMOS	1/2.9" 2M CMOS	1/2.9" 2M CMOS	1/2.9" 2M CMOS
Horizontal Resolution	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
Min. Illumination	Color: 0.09 Lux B/W: 0.009 Lux	Color: 0.04 Lux B/W: 0.004 Lux	Color: 0.11 Lux B/W: 0 Lux (IR LED on)	Color: 0.11 Lux B/W: 0 Lux (IR LED on)	Color: 0.11 Lux B/W: 0 Lux (IR LED on)	Color: 0.11 Lux B/W: 0 Lux (IR LED on)
Lens	-	-	3.2 ~ 10mm (3.1x) motorized V/F (F1.6)	3.2 ~ 10mm (3.1x) V/F (F1.6)	3.2 ~ 10mm (3.1x) motorized V/F (F1.6)	3.2 ~ 10mm (3.1x) V/F (F1.6)
IR Viewable Length	-	-	30m (98.43ft)	30m (98.43ft)	20m (65.62ft)	20m (65.62ft)
Angular Field of View	-	-	H: 106.4°(Wide) ~ 32.2°(Tele) / V: 56.2°(Wide) ~ 18.1°(Tele) / D: 129.4°(Wide) ~ 37.0°(Tele)	H: 106.4°(Wide) ~ 32.2°(Tele) / V: 56.2°(Wide) ~ 18.1°(Tele) / D: 129.4°(Wide) ~ 37.0°(Tele)	H: 106.4°(Wide) ~ 32.2°(Tele) / V: 56.2°(Wide) ~ 18.1°(Tele) / D: 129.4°(Wide) ~ 37.0°(Tele)	H: 106.4°(Wide) ~ 32.2°(Tele) / V: 56.2°(Wide) ~ 18.1°(Tele) / D: 129.4°(Wide) ~ 37.0°(Tele)
Focus Control	Simple Focus	Manual	Simple Focus	Manual	Simple Focus	Manual
Pan / Tilt / Rotate	-	-	-	-	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°
OPERATIONAL						
Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)	WDR (120dB)
Digital Noise Reduction	SSNRIV	SSNRIV	SSNRIV	SSNRIV	SSNRIV	SSNRIV
Motion Detection	Support	Support	Support	Support	Support	Support
Privacy Masking	4 Zones	4 Zones	4 Zones	4 Zones	4 Zones	4 Zones
FEATURES						
Alarm I/O	0 / 1, External D/N 1	0 / 1, External D/N 1	MD Output 1	MD Output 1	MD Output 1	MD Output 1
Communication	AHD: ACP (AHD Coax Protocol), CVBS: Pelco-C (Coaxitron), CCP (CVI Coax Protocol), TCP (TVI Coax Protocol), RS-485	AHD: ACP (AHD Coax Protocol), CVBS: Pelco-C (Coaxitron), CCP (CVI Coax Protocol), TCP (TVI Coax Protocol), RS-485	AHD: ACP (AHD Coax Protocol), CVBS: Pelco-C (Coaxitron), CCP (CVI Coax Protocol), TCP (TVI Coax Protocol)	AHD: ACP (AHD Coax Protocol), CVBS: Pelco-C (Coaxitron), CCP (CVI Coax Protocol), TCP (TVI Coax Protocol)	AHD: ACP (AHD Coax Protocol), CVBS: Pelco-C (Coaxitron), CCP (CVI Coax Protocol), TCP (TVI Coax Protocol)	AHD: ACP (AHD Coax Protocol), CVBS: Pelco-C (Coaxitron), CCP (CVI Coax Protocol), TCP (TVI Coax Protocol)
Environment Protection	-	-	IP66, IK10	IP66, IK10	-	-
Operating Temperature	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)
Power	Max. 6W (24V AC & 12V DC)	Max. 3.5W (24V AC & 12V DC)	Max. 6.0W (24V AC & 12V DC)	Max. 6.0W (24V AC & 12V DC)	Max. 4.2W (24V AC & 12V DC)	Max. 4.2W (24V AC & 12V DC)
Dimensions (WxHxD) / Weight	73.1 x 67.2 x 123.9mm (2.9" x 2.6" x 4.9") 287g (0.63 lb)	68.4 x 59.6 x 92.7mm (2.69" x 2.35" x 3.65") 175.5g (0.39 lb)	Ø78.0 x 260.0mm (Ø3.07" x 10.24") (Without SunShield) 922g (2.03 lb)	Ø78.0 x 260.0mm (Ø3.07" x 10.24") (Without SunShield) 922g (2.03 lb)	Ø119.8 x 98.8mm (Ø4.72" x 3.89") 304g (0.67 lb)	Ø119.8 x 98.8mm (Ø4.72" x 3.89") 304g (0.67 lb)
Additional Features	Video transmission up to 500m (5C2V Coaxial Cable)	Video transmission up to 500m (7.5-5 Coaxial Cable)	Video transmission up to 500m (7.5-5 Coaxial Cable)	Video transmission up to 500m (7.5-5 Coaxial Cable)	Video transmission up to 500m (7.5-5 Coaxial Cable)	Video transmission up to 500m (7.5-5 Coaxial Cable)

Preliminary



WISENET HD+
HCV-6080R

Preliminary



WISENET HD+
HCV-6070R



WISENET HD+
HCM-9020VQ



WISENET HD+
HCP-6320HA/6320A



WISENET HD+
SCB-6003

	2MP	2MP	2MP	2MP	2MP
TV Lines / Resolutions	2MP	2MP	2MP	2MP	2MP
Imaging Device	1/2.9" 2M CMOS	1/2.9" 2M CMOS	1/3" 2M CMOS Sensor x 4ea	1/2.8" 2.38M CMOS	1/2.9" 2M CMOS
Horizontal Resolution	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
Min. Illumination	Color: 0.11 Lux B/W: 0 Lux (IR LED on)	Color: 0.11 Lux B/W: 0 Lux (IR LED on)	Color: 0.1 Lux (4mm) / 0.01 Lux (6mm) B/W: 0.01 Lux (4mm) / 0.01 Lux (6mm)	Color: 0.2 Lux B/W: 0.01 Lux	Color: 0.04 Lux B/W: 0.004 Lux
Lens	3.2 ~ 10mm (3.1x) motorized V/F (F1.6)	3.2 ~ 10mm (3.1x) V/F (F1.6)	4mm x 2ea, 6mm x 2ea	4.44 ~ 142.6mm (Optical 32x) F1.6(Wide) / F4.4(Tele)	-
IR Viewable Length	30m (98.43ft)	30m (98.43ft)	-	-	-
Angular Field of View	H: 106.4°(Wide) ~ 32.2°(Tele) / V: 56.2°(Wide) ~ 18.1°(Tele) / D: 129.4°(Wide) ~ 37.0°(Tele)	H: 106.4°(Wide) ~ 32.2°(Tele) / V: 56.2°(Wide) ~ 18.1°(Tele) / D: 129.4°(Wide) ~ 37.0°(Tele)	[4mm] H: 80.20° / V: 43.50° / D: 95.24° [6mm] H: 51.66° / V: 30.46° / D: 60.78°	H: 62.8°(Wide) ~ 2.23°(Tele) / V: 36.8°(Wide) ~ 1.26°(Tele)	-
Focus Control	Simple Focus	Manual	Fixed	Auto / Manual / One push	-
Pan / Tilt / Rotate	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	20° ~ 60° / 0° / 355°	360° Endless / 210° (-15° ~ 195°) / -	-
Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (120dB)	WDR (120dB)	WDR (100dB)	WDR (120dB)	BLC / DWDR
Digital Noise Reduction	SSNRIV	SSNRIV	Off / Low / Middle / High	SSNRIII	SSNRIV
Motion Detection	Support	Support	Support	Support	Support
Privacy Masking	4 Zones	4 Zones	16 Zones	32 Zones	4 Zones
Alarm I/O	MD Output 1	MD Output 1	0 / 4	4 / 2 (Relay)	0 / 1
Communication	AHD: ACP (AHD Coax Protocol), CVBS: Pelco-C (Coaxitron), CCP (CVI Coax Protocol), TCP (TVI Coax Protocol)	AHD: ACP (AHD Coax Protocol), CVBS: Pelco-C (Coaxitron), CCP (CVI Coax Protocol), TCP (TVI Coax Protocol)	Pelco-C (Coaxitron), Pelco-D (RS485)	RS-485: Samsung-T/E, Pelco-P/D, Sungjin, Panasonic, Honeywell, AD, Vicon, Bosch, GE AHD: ACP (AHD Coax protocol)	AHD: ACP (AHD Coax Protocol), CVBS: Pelco-C (Coaxitron), RS-485
Environment Protection	IP66, IK10	IP66, IK10	IP66, IK10	IP66, IK10 (HCP-6320HA), IK10 (With SHP-3701H) (HCP-6320A)	-
Operating Temperature	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-30°C ~ +50°C (-22°F ~ +122°F) * Start up above -10°C (+14°F)	-50°C ~ +55°C (-58°F ~ +131°F) (HCP-6320HA), -10°C ~ +55°C (+14°F ~ +131°F) (HCP-6320A)	-10°C ~ +55°C (+14°F ~ +131°F)
Power	Max. 4.2W (24V AC & 12V DC)	Max. 4.2W (24V AC & 12V DC)	Max. 7.3W, TDN On (24V AC) Max. 6.7W, TDN On (12V DC)	Max. 24.0W / 65.0W - Heater off / on (24V AC) (HCP-6320HA) Max. 20.0W (24V AC) (HCP-6320A)	Max. 3.5W (24V AC & 12V DC)
Dimensions (WxHxD) / Weight	Ø119.8 x 98.8mm (Ø4.72" x 3.89") 304g (0.67 lb)	Ø119.8 x 98.8mm (Ø4.72" x 3.89") 304g (0.67 lb)	Ø199 x 89.5mm (7.83" x 3.52") 2Kg (4.41 lb)	Ø220.0 x 293.6mm (Ø8.66" x 11.56") 3.3Kg (7.28 lb) (SNP-6320HA), Ø152.0 x 218.0mm (Ø5.98" x 8.58") 2.2Kg (4.85 lb) (SNP-6320A)	68.4 x 59.6 x 92.7mm (2.69" x 2.35" x 3.65") 175.5g (0.39 lb)
Additional Features	Video transmission up to 500m (75-5 Coaxial Cable)	Video transmission up to 500m (75-5 Coaxial Cable)	Multi-directional camera	Defog	Defog



WISENET HD+
SCO-6083R



WISENET HD+
SCO-6023R



WISENET HD+
SCD-6083R



WISENET HD+
SCD-6023R



WISENET HD+
SCD-6013



WISENET HD+
SCV-6083R



WISENET HD+
SCV-6023R

TV Lines / Resolutions		2MP	2MP	2MP	2MP	2MP	2MP	2MP
VIDEO	Imaging Device	1/2.9" 2M CMOS	1/2.9" 2M CMOS	1/2.9" 2M CMOS	1/2.9" 2M CMOS	1/3" 2M CMOS	1/2.9" 2M CMOS	1/2.9" 2M CMOS
	Horizontal Resolution	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
	Min. Illumination	Color: 0.11 Lux B/W: 0 Lux (IR LED on)	Color: 0.25 Lux B/W: 0 Lux (IR LED on)	Color: 0.11 Lux B/W: 0 Lux (IR LED on)	Color: 0.25 Lux B/W: 0 Lux (IR LED on)	Color: 0.1 Lux B/W: 0.01 Lux	Color: 0.11 Lux B/W: 0 Lux (IR LED on)	Color: 0.25 Lux B/W: 0 Lux (IR LED on)
	Lens	2.8 ~ 12mm (4.3x) V/F (F1.4)	4mm fixed (F 2.1)	2.8 ~ 12mm (4.3x) V/F (F1.4)	4mm fixed (F 2.1)	2.8mm fixed (F1.8)	2.8 ~ 12mm (4.3x) V/F (F1.4)	4mm fixed (F 2.1)
	IR Viewable Length	30m (98.43ft)	20m (65.62ft)	20m (65.62ft)	20m (65.62ft)	-	30m (98.43ft)	20m (65.62ft)
	Angular Field of View	H: 103.8°(Wide) ~ 32.4°(Tele) / V: 53.7°(Wide) ~ 18.4°(Tele) / D: 121.9°(Wide) ~ 37.1°(Tele)	H: 72.2° / V: 52.9° / D: 94.3°	H: 103.8°(Wide) ~ 32.4°(Tele) / V: 53.7°(Wide) ~ 18.4°(Tele) / D: 121.9°(Wide) ~ 37.1°(Tele)	H: 72.2° / V: 52.9° / D: 94.3°	H: 108.7° / V: 60.6° / D: 125.4°	H: 103.8°(Wide) ~ 32.4°(Tele) / V: 53.7°(Wide) ~ 18.4°(Tele) / D: 121.9°(Wide) ~ 37.1°(Tele)	H: 72.2° / V: 52.9° / D: 94.3°
	Focus Control	Manual	Fixed	Manual	Fixed	Fixed	Manual	Fixed
	Pan / Tilt / Rotate	-	-	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°	0° ~ 350° / 0° ~ 67° / 0° ~ 355°
OPERATIONAL	Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)
	Backlight Compensation	BLC / DWDR	BLC / DWDR	BLC / DWDR	BLC / DWDR	DWDR / BLC / HLC	BLC / DWDR	BLC / DWDR
	Digital Noise Reduction	SSNRIV	SSNRIV	SSNRIV	SSNRIV	SSNRIV	SSNRIV	SSNRIV
	Motion Detection	Support	Support	Support	Support	Support	Support	Support
	Privacy Masking	4 Zones	4 Zones	4 Zones	4 Zones	4 Zones	4 Zones	4 Zones
FEATURES	Alarm I/O	0 / 1	-	0 / 1	-	-	0 / 1	-
	Communication	AHD : ACP (AHD Coax Protocol), CVBS : Pelco-C (Coaxitron)	AHD : ACP (AHD Coax Protocol), CVBS : Pelco-C (Coaxitron)	AHD : ACP (AHD Coax Protocol), CVBS : Pelco-C (Coaxitron)	AHD : ACP (AHD Coax Protocol), CVBS : Pelco-C (Coaxitron)	AHD : ACP (AHD Coax Protocol), CVBS : Pelco-C (Coaxitron)	AHD : ACP (AHD Coax Protocol), CVBS : Pelco-C (Coaxitron)	AHD : ACP (AHD Coax Protocol), CVBS : Pelco-C (Coaxitron)
	Environment Protection	IP66, IK10	IP66	-	-	-	IP66, IK10	IP66, IK10
	Operating Temperature	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)
	Power	Max. 6.0W (24V AC & 12V DC)	Max. 4.2W (12V DC)	Max. 4.2W (24V AC & 12V DC)	Max. 4.2W (12V DC)	Max. 2.5w (12V DC)	Max. 4.2W (24V AC & 12V DC)	Max. 4.2W (12V DC)
	Dimensions (WxHxD) / Weight	Ø78.0 x 260.0mm (3.07" x 10.24") (Without SunShield) 922g (2.03 lb)	Ø58.6 x 165.2mm (Ø2.31" x 6.5") (Without Sunshield) 208g (0.46 lb)	Ø119.8 x 98.8mm (Ø4.72" x 3.89") 304g (0.67 lb)	Ø110.0 x 86.0mm (Ø4.33" x 3.39") 242g (0.53 lb)	Ø110.0 x 86.0mm (Ø4.33" x 3.39") 231g (0.51 lb)	Ø137.0 x 106.1mm (Ø5.39" x 4.18") 716g (1.58 lb)	Ø137.0 x 94.0mm (Ø5.39" x 3.7") 560g (1.23 lb)
	Additional Features	Defog	Defog	Defog	Defog	Defog	Defog	Defog



WISENET HD+
SRD-1694



WISENET HD+
SRD-1685



WISENET HD+
SRD-1684/893/493



WISENET HD+
SRD-894



WISENET HD+
SRD-494

		16CH	16CH	16CH/8CH/4CH	8CH	4CH
Channel		16CH	16CH	16CH/8CH/4CH	8CH	4CH
OS	Embedded	Linux	Linux	Linux	Linux	Linux
Live	Frame Rate (NTSC / PAL)	480fps / 400fps	480fps / 400fps	480fps / 400fps (SRD-1684) 240fps / 200fps (SRD-893) 120fps / 100fps (SRD-493)	240fps / 200fps	120fps / 100fps
	Max. Record Rate / NTSC	480fps@1920 x 1080	480fps@1280 x 720 192fps@1080p	240fps@1920 x 1080 (SRD-1684/893) 120fps@1920 x 1080 (SRD-493)	240fps@1920 x 1080	120fps@1920 x 1080
Recording	Max. Record Rate / PAL	400fps@1920 x 1080	400fps@1280 x 720 192fps@1080p	200fps@1920 x 1080 (SRD-1684/893) 100fps@1920 x 1080 (SRD-493)	200fps@1920 x 1080	100fps@1920 x 1080
	Compression	H.264	H.264	H.264	H.264	H.264
	Inputs	16CH : AHD, NTSC, PAL	16CH : AHD, NTSC, PAL	16CH : AHD, NTSC, PAL (SRD-1684) 8CH : AHD, NTSC, PAL (SRD-893) 4CH : AHD, NTSC, PAL (SRD-493)	8CH : AHD, NTSC, PAL	4CH : AHD, NTSC, PAL
Audio	Inputs	16CH (Built-in 4CH)	16CH (Built-in 4CH)	1CH	8CH (Built-in 4CH)	4CH
Storage	Internal HDD	Up to 8 SATA HDDs	Up to 4 SATA HDDs	1 SATA HDD	Up to 4 SATA HDDs	Up to 2 SATA HDDs
Monitors	VGA	Yes	Yes	Yes	Yes	Yes
	HDMI	Yes	Yes	Yes	Yes	Yes
	Spot Composite	1CH (Digital)	1CH (Digital)	-	2CH (Digital)	2CH (Digital)
Connections	USB	2 Ports	2 Ports	2 Ports	2 Ports	2 Ports
	e-SATA	2 External SATA Ports	2 External SATA Ports	-	2 External SATA Ports	-
	Mouse	Yes	Yes	Yes	Yes	Yes
Network	Remote Users	Search 3 / Live Unicast 10 / Live Multicast 20	Search 3 / Live Unicast 10 / Live Multicast 20	Search 3 / Live Unicast 10 / Live Multicast 20	Search 3 / Live Unicast 10 / Live Multicast 20	Search 3 / Live Unicast 10 / Live Multicast 20
	Transmission	1080p, 720p, 4CIF, 2CIF, CIF	1080p, 720p, 4CIF, 2CIF, CIF	4CIF, 2CIF, CIF	1080p, 720p, 4CIF, 2CIF, CIF	1080p, 720p, 4CIF, 2CIF, CIF
	Monitoring	SmartViewer, WebViewer, SSM	SmartViewer, WebViewer, SSM	SmartViewer, WebViewer, Mobile Viewer, SSM	SmartViewer, WebViewer, SSM	SmartViewer, WebViewer, SSM
PTZ Control	Coax Protocol	NTSC / PAL : Samsung CCVC, Pelco-C (Coaxitron) AHD : ACP (AHD Coax Protocol)	NTSC / PAL : Samsung CCVC, Pelco-C (Coaxitron) AHD : ACP (AHD Coax Protocol)	NTSC / PAL : PTZ control via coaxial cable Pelco-C (Coaxitron) AHD : ACP (AHD Coax Protocol)	NTSC / PAL : Samsung CCVC, Pelco-C (Coaxitron) AHD : ACP (AHD Coax Protocol)	NTSC / PAL : Samsung CCVC, Pelco-C (Coaxitron) AHD : ACP (AHD Coax Protocol)
	RS-485 Protocol	Samsung-T/E, Pelco-D/P, Panasonic, Phillips, AD, DIAMOND, ERNA, KALATEL, VCL TP, VICON, ELMO, GE	Samsung-T/E, Pelco-D/P, Panasonic, Phillips, AD, DIAMOND, ERNA, KALATEL, VCL TP, VICON, ELMO, GE	Samsung-T/E, Pelco-D/P, Panasonic, Phillips, AD, VICON, GE	Samsung-T/E, Pelco-D/P, Panasonic, Phillips, AD, DIAMOND, ERNA, KALATEL, VCL TP, VICON, ELMO, GE	Samsung-T/E, Pelco-D/P, Panasonic, Phillips, AD, DIAMOND, ERNA, KALATEL, VCL TP, VICON, ELMO, GE

* Option : Audio extension cable

© 2017 Hanwha Techwin Co., LTD. All rights reserved.

* The latest product information / sepecification can be found at hanwha-security.com



**BEYOND
SCB-5005**



**BEYOND
SCB-5003**



**BEYOND
SCB-5000**



**BEYOND
SCO-5083R**



**BEYOND
SCD-5083**



**BEYOND
SCD-5080**

	BEYOND SCB-5005	BEYOND SCB-5003	BEYOND SCB-5000	BEYOND SCO-5083R	BEYOND SCD-5083	BEYOND SCD-5080
TV Lines	1000TVL	1000TVL	1000TVL	1000TVL	1000TVL	1000TVL
Imaging Device	1/3" 1.3M CMOS	1/3" 1.3M CMOS	1/3" 1.3M CMOS	1/3" 1.3M CMOS	1/3" 1.3M CMOS	1/3" 1.3M CMOS
Horizontal Resolution	Color: 1000TV lines	Color: 1000TV lines	Color: 1000TV lines	Color: 1000TV lines	Color: 1000TV lines	Color: 1000TV lines
Min. Illumination	Color: 0.01 Lux B/W: 0.001 Lux	Color: 0.01 Lux B/W: 0.001 Lux	Color: 0.01 Lux	Color: 0.02 Lux B/W: 0 Lux (IR LED on)	Color: 0.01 Lux B/W: 0.001 Lux	Color: 0.02 Lux
VIDEO Lens	-	-	-	3 ~ 10mm (3.3x) V/F (F1.4)	2.8 ~ 10.5mm (3.8x) V/F (F1.2)	3 ~ 10mm (3.3x) V/F (F1.4)
IR Viewable Length	-	-	-	50m (164.04ft)	-	-
Angular Field of View	-	-	-	H: 82.0°(Wide) ~ 26.5°(Tele) / V: 59.7°(Wide) ~ 19.9°(Tele)	H: 91.5°(Wide) ~ 27.7°(Tele) / V: 68.3°(Wide) ~ 20.8°(Tele)	H: 82.0°(Wide) ~ 26.5°(Tele) / V: 59.7°(Wide) ~ 19.9°(Tele)
Pan / Tilt / Rotate	-	-	-	-	0° ~ 354° / 0° ~ 68° / 0° ~ 355°	0° ~ 354° / 0° ~ 68° / 0° ~ 355°
OPERATIONAL Day & Night	True (ICR)	True (ICR)	Electrical	True (ICR)	True (ICR)	Electrical
Backlight Compensation	WDR (120dB)	WDR (120dB)	BLC / HLC	WDR (120dB)	WDR (120dB)	BLC / HLC
Digital Noise Reduction	SSNRIV	SSNRIV	SSNRIV	SSNRIV	SSNRIV	SSNRIV
Motion Detection	Support	Support	Support	Support	Support	Support
Privacy Masking	24 Zones (4 Points Polygonal Masking)	24 Zones (4 Points Polygonal Masking)	24 Zones (4 Points Polygonal Masking)	24 Zones (4 Points Polygonal Masking)	24 Zones (4 Points Polygonal Masking)	24 Zones (4 Points Polygonal Masking)
Intelligent Video Analytics	Fence, (Dis)Appear, Counting	Fence, (Dis)Appear, Counting	-	Fence, (Dis)Appear, Counting	Fence, (Dis)Appear, Counting	-
FEATURES Alarm I/O	0 / 1	0 / 1	-	0 / 1	0 / 1	-
Communication	Coax: Pelco-C (Coaxitron), RS-485	Coax: Pelco-C (Coaxitron), RS-485	Coax: Pelco-C (Coaxitron)	Coax: Pelco-C (Coaxitron), RS-485	Coax: Pelco-C (Coaxitron)	Coax: Pelco-C (Coaxitron)
Environment Protection	-	-	-	IP66, IK10	-	-
Operating Temperature	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-10°C ~ +55°C (+14°F ~ +131°F)	-10°C ~ +55°C (+14°F ~ +131°F)
Power	Max. 6.0W (24V AC & 12V DC)	N/P: Max. 6.0W (24V AC & 12V DC) PH: Max. 6.0W (230V AC)	N/P: Max. 3.7W (24V AC & 12V DC) ND/PD: Max. 2.7W (12V DC) PH: Max. 4.6W (230V AC)	Max. 9.5W (24V AC & 12V DC)	Max. 5.6W (24V AC & 12V DC)	Max. 3.5W (24V AC & 12V DC)
Dimensions (WxHxD) / Weight	73.1 x 67.2 x 123.9mm (2.88" x 2.65" x 4.88") 300g (0.66 lb)	N/P: 68.4 x 59.6 x 92.7mm (2.69" x 2.35" x 3.65") 210g (0.46 lb) PH: 68.3 x 59.6 x 116.6mm (2.69" x 2.35" x 4.59") 411g (0.91 lb)	68.4 x 59.6 x 92.7mm (2.69" x 2.35" x 3.65") N/P/PD: 200g (0.44 lb) ND: 175g (0.39 lb)	Ø78.0 x 272.8mm (3.07" x 10.74") (Without SunShield) 1.5Kg (3.3 1 lb)	Ø119.8 x 101.8mm (Ø4.72" x 4.01") 535g (1.18 lb)	Ø119.8 x 101.8mm (Ø4.72" x 4.01") 520g (1.15 lb)
Additional Features	Simple Focus, P-iris, Digital Image Stabilization, Defog, Tampering	Digital Image Stabilization, Defog, Tampering	Digital Image Stabilization, Defog, Tampering	Digital Image Stabilization, Defog, Tampering	Digital Image Stabilization, Defog, Tampering	Digital Image Stabilization, Defog, Tampering



BEYOND
SCD-5083R



BEYOND
SCV-5085



BEYOND
SCV-5083



BEYOND
SCV-5082



BEYOND
SCV-5083R

	BEYOND SCD-5083R	BEYOND SCV-5085	BEYOND SCV-5083	BEYOND SCV-5082	BEYOND SCV-5083R
VIDEO					
TV Lines	1000TVL	1000TVL	1000TVL	1000TVL	1000TVL
Imaging Device	1/3" 1.3M CMOS	1/3" 1.3M CMOS	1/3" 1.3M CMOS	1/3" 1.3M CMOS	1/3" 1.3M CMOS
Horizontal Resolution	Color: 1000TV lines	Color: 1000TV lines	Color: 1000TV lines	Color: 1000TV lines	Color: 1000TV lines
Min. Illumination	Color: 0.02 Lux B/W: 0 Lux (IR LED on)	Color: 0.01 Lux B/W: 0.001 Lux	Color: 0.01 Lux B/W: 0.001 Lux	Color: 0.02 Lux B/W: 0.002 Lux	Color: 0.02 Lux B/W: 0 Lux (IR LED on)
Lens	3 ~ 10mm (3.3x) V/F (F1.4)	3 ~ 8.5mm (2.8x) motorized V/F (F1.2)	2.8 ~ 10.5mm (3.8x) V/F (F1.2)	3 ~ 10mm (3.3x) V/F (F1.4)	3 ~ 10mm (3.3x) V/F (F1.4)
IR Viewable Length	30m (98.43ft)	-	-	-	30m (98.43ft)
Angular Field of View	H: 82.0°(Wide) ~ 26.5°(Tele) / V: 59.7°(Wide) ~ 19.9°(Tele)	H: 105.5°(Wide) ~ 37.1°(Tele) / V: 57.5°(Wide) ~ 21°(Tele)	H: 91.5°(Wide) ~ 27.7°(Tele) / V: 68.3°(Wide) ~ 20.8°(Tele)	H: 82.0°(Wide) ~ 26.5°(Tele) / V: 59.7°(Wide) ~ 19.9°(Tele)	H: 82.0°(Wide) ~ 26.5°(Tele) / V: 59.7°(Wide) ~ 19.9°(Tele)
Pan / Tilt / Rotate	0° ~ 354° / 0° ~ 68° / 0° ~ 355°	0° ~ 354° / 0° ~ 68° / 0° ~ 355°	0° ~ 354° / 0° ~ 68° / 0° ~ 355°	0° ~ 354° / 0° ~ 68° / 0° ~ 355°	0° ~ 354° / 0° ~ 68° / 0° ~ 355°
OPERATIONAL					
Day & Night	True (ICR)	True (ICR)	True (ICR)	True (ICR)	True (ICR)
Backlight Compensation	WDR (120dB)	WDR (120dB)	WDR (120dB)	BLC / HLC	WDR (120dB)
Digital Noise Reduction	SSNRIV	SSNRIV	SSNRIV	SSNRIV	SSNRIV
Motion Detection	Support	Support	Support	Support	Support
Privacy Masking	24 Zones (4 Points Polygonal Masking)	24 Zones (4 Points Polygonal Masking)	24 Zones (4 Points Polygonal Masking)	24 Zones (4 Points Polygonal Masking)	24 Zones (4 Points Polygonal Masking)
Intelligent Video Analytics	Fence, (Dis)Appear, Counting	Fence, (Dis)Appear, Counting	Fence, (Dis)Appear, Counting	-	Fence, (Dis)Appear, Counting
FEATURES					
Alarm I/O	0 / 1	0 / 1	0 / 1	-	0 / 1
Communication	Coax: Pelco-C (Coaxitron)	Coax: Pelco-C (Coaxitron)	Coax: Pelco-C (Coaxitron)	Coax: Pelco-C (Coaxitron)	Coax: Pelco-C (Coaxitron)
Environment Protection	-	IP66, IK10	IP66, IK10	IP66, IK10	IP66, IK10
Operating Temperature	-10°C ~ +55°C (+14°F ~ +131°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)	-30°C ~ +55°C (-22°F ~ +131°F) * Start up above -10°C (+14°F)
Power	Max. 6.0W (24V AC & 12V DC)	Max. 5.0W (24V AC & 12V DC)	Max. 5.6W (24V AC & 12V DC)	Max. 5.6W (24V AC & 12V DC)	Max. 6.0W (24V AC & 12V DC)
Dimensions (WxHxD) / Weight	Ø119.8 x 101.8mm (Ø4.72" x 4.01") 550g (1.21 lb)	Ø137.0 x 106.1mm (Ø5.39" x 4.18") 772g (1.7 lb)	Ø137.0 x 106.1mm (Ø5.39" x 4.18") 720g (1.59 lb)	Ø137.0 x 106.1mm (Ø5.39" x 4.18") 730g (1.61 lb)	Ø137.0 x 106.1mm (Ø5.39" x 4.18") 750g (1.65 lb)
Additional Features	Digital Image Stabilization, Defog, Tampering	Digital Image Stabilization, Defog, Tampering	Digital Image Stabilization, Defog, Tampering	Digital Image Stabilization, Defog, Tampering	Digital Image Stabilization, Defog, Tampering

ANALOG

DVR



BEYOND
SRD-1676D

BEYOND
SRD-476D

Channel		16CH	4CH
OS	Embedded	Linux	Linux
Live	Frame Rate (NTSC / PAL)	480fps / 400fps	120fps / 100fps
Recording	Max. Record Rate / NTSC	480fps@1280 x 480	120fps@1280 x 480 * P/B : 60fps@1280 x 480, 120fps@960 x 480
	Max. Record Rate / PAL	400fps@1280 x 576	100fps@1280 x 576 * P/B : 50fps@1280 x 576, 120fps@960 x 576
	Compression	H.264	H.264
Video	Inputs	16CH	4CH
	Loop Outputs	Yes	Yes
Audio	Inputs	16CH (Built-in 4CH)	4CH
Storage	Internal HDD	Up to 4 SATA HDDs	Up to 1 SATA HDD
	External HDD	Up to 2 Expansion Bays	-
Monitors	VGA	Yes	Yes
	HDMI	Yes	Yes
	Main Composite	-	-
	Spot Composite	2CH (Digital)	2CH (Digital 1CH / Analog 1CH)
Connections	USB	2 Ports	2 Ports
	e-SATA	2 External SATA Ports	-
	DVD Writer (Backup)	Yes	Yes
	Mouse	Yes	Yes
Network	Remote Users	Search 3 / Live Unicast 10 / Live Multicast 20	Search 3 / Live Unicast 10 / Live Multicast 20
	Transmission	4CIF, 2CIF, CIF	4CIF, 2CIF, CIF
	Monitoring	SmartViewer, WebViewer, SSM	SmartViewer, WebViewer, SSM
Removable BNC Panel		-	-
PTZ Control	Coax Protocol	Samsung CCVC, Pelco-C	Samsung CCVC, Pelco-C
	RS-485 Protocol	Samsung-T/E, Pelco-D/P, Panasonic, Phillips, AD, DIAMOND, ERNA, KALATEL, VCL TP, VICON, ELMO, GE	Samsung-T/E, Pelco-D/P, Panasonic, Phillips, AD, DIAMOND, ERNA, KALATEL, VCL TP, VICON, ELMO, GE

• Option : Audio extension cable * Coaxial communication not supported

MONITOR / CONTROLLER

LED Monitor



SMT-4933



SMT-4032A



SMT-3232A



SMT-2731



SMT-2233



SMT-1935



SMT-1931



SMT-1914

Screen Size	49" (UHD)	40"	32"	27"	22"	19"	19"	19"
Resolution (pixels HxV)	3,840 x 2,160	1,920 x 1,080	1,920 x 1,080	1,920 x 1,080	1,920 x 1,080	1,280 x 1,024	1,366 x 768	1,280 x 1,024
Video In/Out	-	1	1	2/2	2/2	2/2	2/2	-
VGA	1	1	1	1	1	1	1	1
DVI / HDMI	2/4	1/1	1/1	0/1	0/1	0/1	0/1	-
USB	Yes (S/W Update Only)	Yes	Yes	-	-	-	-	-
Audio In (Stereo)	1	2	2	2	2	2	2	-
Contrast Ratio	4,700:1	5,000:1	5,000:1	1,000:1	1,000:1	1,000:1	1,000:1	1,000:1
Aspect Ratio	16:9	16:9	16:9	16:9	16:9	4:3	16:9	4:3
Response Time	8ms	8ms	8ms	5ms	5ms	5ms	5ms	5ms
Brightness	500cd/m ²	350cd/m ²	350cd/m ²	300cd/m ²	250cd/m ²	250cd/m ²	250cd/m ²	250cd/m ²
Tempered Glass Screen	-	-	-	Yes	Yes	Yes	Yes	Yes
Picture In Picture	-	Yes	Yes	-	-	-	-	Yes
Built-in Speakers	Yes	Yes	Yes	Yes	Yes	Yes	Yes	-
Stand	General (Optional)	General (Optional)	General (Optional)	Standard	Standard	Standard	Standard	Standard
Power	100V ~ 240V AC	100V ~ 240V AC	100V ~ 240V AC	100V ~ 240V AC	100V ~ 240V AC	100V ~ 240V AC	100V ~ 240V AC	100V ~ 240V AC
Additional Features	Temperature Sensor, 24/7 (50,000 hour), Full HD 4 Picture by Picture Support	Wi-Fi module Embedded	Wi-Fi module Embedded	-	-	-	-	-

Controller / PoE Extender



SPC-7000



SPC-2000








SPC-2010



SPC-1010

Model	SPC-7000	SPC-2000	SPC-2010	SPC-1010
Features	<p>Network/Analog Cameras / NVR / DVR / SSM Controller</p> <ul style="list-style-type: none"> • 5" TFT Touch LCD • Network Camera / SSM / Analog Camera / DVR Control • User-Friendly Design and Easy-to-Use Keypad • 3 Axis Joystick to Control PTZ Function • Detachable Joystick / Jogshuttle for Universe Use (Right / Left Hand Use) • USB Interface Support (1ea for SSM, 1ea for Image Snapshot / Upgrade) • Fast Camera-Tile Mapping, Config Import / Export 	<p>Network Controller</p> <ul style="list-style-type: none"> • Superior System Compatibility • 3D Joystick Control • Quick and Easy Installation • SSM Support 	<p>PTZ / DVR System Controller</p> <ul style="list-style-type: none"> • Control up to 255 PTZ Cameras / DVRs • Built-in 3 Axis Twist Zoom Joystick • Built-in Jog Shuttle • 16 x 2 Character LCD Display • RS-485 and RS-422 Interface 	<p>PTZ Control Keyboard</p> <ul style="list-style-type: none"> • Control up to 255 PTZ Cameras • Multi Protocols Supports • OSD Menu, 3D Joystick Control • RS-485 and RS-422 Interface

LENS

Lens Description	Model	Image	Mount	Image Format	Resolution	Focal Length	Back Focal Length	Zoom Ratio	F. No	Angle of View	Operation			Dimensions W x H x D (mm / inch)	Weight (g / lb)
											Iris	Focus	Zoom		
Varifocal Lens	SLA-M8550D	 New	CS	1/2.8"	3Megapixel	8.5 ~ 50mm (0.33" ~ 1.97")	9.4 ~ 10.7mm (0.37" ~ 0.42")	5.88	F1.6	64.0° ~ 6.9°	DC			46 x 60 x 58.2mm (1.81" x 2.36" x 2.29")	80g (0.17 lb)
	SLA-M2890DN					2.8 ~ 9mm (0.11" ~ 0.35")	7.5 ~ 15.9mm (0.3" ~ 0.63")	3.2	1.2	134.2° ~ 42.7°				45.0 x 51.5 x 54.3mm (1.77" x 2.03" x 2.14")	84.0g (0.19 lb)
	SLA-M2890PN			P-Iris	Manual	Manual	82.1g (0.18 lb)								
	SLA-2812DN			1/3"	520K pixel	2.8 ~ 12mm (0.11" ~ 0.47")	20.2 ~ 8.1mm (0.8" ~ 0.32")	4.2	1.3	133.0° ~ 29.7°	DC			37.5 x 48.0 x 56.0mm (1.48" x 1.89" x 2.2")	71g (0.16 lb)
	SLA-550DV					5 ~ 50mm (0.2" ~ 1.97")	10.5 ~ 10.6mm (0.41" ~ 0.42")	10	1.3	64.0° ~ 6.9°				45.0 x 56.2 x 57.8mm (1.77" x 2.21" x 2.28")	100g (0.22 lb)

PERIPHERALS



SHP-1680F



SHP-3701H



SHP-3701F



SHD-3000F1



SHD-3000F2



SHD-3000F3

In-Ceiling Housing for PTZ & Dome
 • For indoor applications
 • Polycarbonate
 • Can be used with
 XNP-6120H
 XNV-6120/6120R/6085
 XND-6085/6085V

Outdoor Housing for PTZ Dome
 • For outdoor applications
 • Weatherproof rated to IP66
 • Aluminium + Polycarbonate
 • IK10 vandal resistant
 • Can be used with
 SNP-3300A/3301/3302/3350/3370/3371/
 3750/5200/5300/5320/5321/5430/
 6200/6201/6320/6321/L5233/L6233
 SCP-2250/2251/2270/2271/2273/2330/
 2370/2371/2373/2430/3250/3370/
 3371/3430

In-Ceiling Housing for Dome
 • For indoor applications
 • Polycarbonate
 • Can be used with
 SNP-3300A/3301/3302/3350/3370/3371/
 3750/5200/5300/5320/5321/5430/
 6200/6201/6320/6321/L5233/L6233
 SCP-2250/2251/2270/2271/2273/2330/
 2370/2371/2373/2430/3250/3370/
 3371/3430

In-Ceiling Housing for PTZ Dome
 • For indoor applications
 • Polycarbonate
 • Can be used with
 PNV-9080R
 XNV-6080/6080R/8080R
 SND-5083/5084/5084R/6083/
 6084/6084R/7084/7084R
 SNV-5084/5084R/6084/6084R/6085R/
 7084/7084R/8080/8081R
 SCD-6081R
 SCV-6081R

In Ceiling Housing for Dome
 • For indoor applications
 • Polycarbonate
 • Can be used with
 QND-6070R/7080R
 SND-6011R/L5083R/L6083R
 SCD-5080/5082/5083/5083R/
 6021/6083R
 SUD-5082
 HCD-7070R/6080R/6070R

In Ceiling Housing for Dome
 • For indoor applications
 • Polycarbonate
 • Can be used with
 QNV-6070R/7080R
 SNV-L5083R/L6083R
 SCV-5082/5082R/5083/5083R/5085/
 6023R/6083R
 HCV-7070R/7010R/7020R/ 7030R/
 6080R/6070R



SHD-3000F4



SHF-1500F



SBP-300HM1



SBP-301HM2



SBP-301HM3



SBP-301HM4/300HM5

In Ceiling Housing for Dome
 • For indoor applications
 • Polycarbonate
 • Can be used with
 PND-9080R
 XND-6080RV/6080V/8080RV

In-Ceiling Housing for Dome
 • For indoor applications
 • Polycarbonate
 • Can be used with
 PNF-9010R
 XNF-8010R

Hanging Mount
 • Aluminum
 • Can be used with
 SNP-3300A/3301/3302/3350/3370/
 3371/3750/5200/6200/3120
 SCP-2250/2251/2430/3250/3430/
 2120/3120/2270/2330/2370/3370
 SBP-300CM/300LM/300WM/300WM1

Hanging Mount
 • Aluminum
 • Can be used with
 QNV-6070R/7080R
 SNV-1080/1080R/L5083R/L6083R
 SND-5083/5084/5084R/6083/6084/6084R/
 7084/7084R
 SCV-2081/2081R/2082R/3081/3082/3083/5082/
 5082R/5083/5083R/5085/6023R/6083R
 SCD-6081R
 HCV-7070R/6080R/6070R
 SBP-300CM/300LM/300WM/300WM1

Hanging Mount
 • Aluminum
 • Can be used with
 SNV-3080/3082/3120/5080/5080R/
 7080/7080R/7082
 SNP-5300/5320/5321/5430/6201/
 6320/6321/L5233/L6233
 SCV-2060/2080/3080/3120
 SCP-2271/2273/2371/2373/3371
 SBP-300CM/300LM/300WM/300WM1

Hanging Mount for
 3M / 5M Fisheye Cameras
 • Aluminum
 • Can be used with
 SNF-7010/7010V/7010VM
 SBP-300CM/300LM/300WM/300WM1
 (SBP-301HM4)
 • Can be used with
 SNF-8010/8010VM
 SBP-300CM/300LM/300WM/300WM1
 (SBP-301HM5)



SBP-300HM6



SBP-300HM7



SBP-300HM8



SBP-122HM



SBP-168HM



SBP-201HM



SBP-317HM

Hanging Mount
 • Aluminum
 • Can be used with
 PNV-9080R
 XNV-6080/6080R/6120/6120R/8080R
 SNV-5084/5084R/6084/6084R/6085R/
 7084/7084R/8080/8081R
 SCV-6081R
 SBP-300CM/300LM/300WM/300WM1

Hanging Mount
 • Aluminum
 • Can be used with
 XND-6010/6020/8020R/8030R/8040R
 QND-6010R/6020R/6030R/
 7010R/7020R/7030R
 SND-L5013/L6012/L6013/L6013R/L6014R
 SNV-6013
 SCD-6023R
 HCD-7010R/7020R/7030R
 SBP-300CM/300LM/300WM/300WM1

Hanging Mount
 • Aluminum
 • Can be used with
 PND-9080R
 XND-6080RV/6080V/6085V/8080RV
 SND-6084R/6084/6083/
 5084R/5084/5083
 SCD-6081R
 SBP-300CM/300LM/300WM/300WM1


















Hanging Mount
 • Aluminum
 • Can be used with
 XNV-6010/6020/8020R/8030R/8040R
 QNV-6010R/6020R/6030R/7010R/
 7020R/7030R
 QND-6070R/7080R
 SCD-5080/5082/5083/5083R/6021/6083R
 SND-6011R/L5083R/L6083R
 SUD-5082
 HCD-7070R/6080R/6070R
 HCV-7010R/7020R/7030R
 SBP-300CM/300LM/300WM/300WM1

Hanging Mount
 • Aluminum
 • Can be used with
 XNP-6120H

Hanging Mount
 • Aluminum
 • Can be used with
 PNM-9020V
 (SBP-201HM)
 • Can be used with
 PNM-9080VQ/9081VQ
 (SBP-317HM)

Hanging Mount
 • Aluminum
 • Can be used with
 PNM-9020V
 (SBP-201HM)
 • Can be used with
 PNM-9080VQ/9081VQ
 (SBP-317HM)

PERIPHERALS

 <p>SBP-300HF/301HF/302HF</p>	 <p>SBP-300TM1</p>	 <p>SBP-160TM</p>	 <p>SBP-300CM</p>	 <p>SBP-300WM1/300WM</p>	 <p>SBP-300LM</p>
<p>Built-in SFP Install Base for PTZ Cameras</p> <ul style="list-style-type: none"> Aluminum LC SFP port type 100Mbps Ethernet speed (Default speed : 1000Mbps) IEEE 802.3u, IEEE 802.3z Support Audio input/output, 3.5mm type 24V AC, IP66, IK10, -50°C to +55°C Can use with SNP-6320H/5430H (SBP-300HF) Can use with SNP-6321H/5321H/L6233H/L5233H (SBP-301HF) Can use with PNP-9200RH/XNP-6370RH (SBP-302HF) 	<p>Tilt Mount for 3M/5M Fisheye Cameras</p> <ul style="list-style-type: none"> Poly Carbonate Can be used with SNF-8010/8010VM (SBP-300TM1) 	<p>Tilt Mount</p> <ul style="list-style-type: none"> Aluminum Can be used with PNV-9080R XNV-6080/6080R/8080R SNV-5084/5084R/6084/6084R/6085R/7084/7084R/8080/8081R SCV-6081R 	<p>Ceiling Mount</p> <ul style="list-style-type: none"> Aluminum + SECC Can be used with hanging mount and outdoor PTZ 	<p>Wall Mount</p> <ul style="list-style-type: none"> Aluminum + SECC Can be used with SBP-300NB/300B/300PM/300KM 	<p>Parapet Mount</p> <ul style="list-style-type: none"> Aluminum + SECC Can be used with hanging mount and outdoor PTZ
 <p>SBP-137WM</p>	 <p>SBP-120WM</p>	 <p>SBP-300PM/302PM</p>	 <p>SBP-300KM</p>	 <p>SBP-300PM</p>	
<p>Wall Mount</p> <ul style="list-style-type: none"> Alluminum and Poly Carbonate Can be used with QNV-6010R/6020R/6030R/6070R/7010R/7020R/7030R/7080R XNV-6010/602/8020R/8030R/8040R HCV-6070R/6080R/7010R/7020R/7030R/7070R/SCV-5082/5082R/5083/5083R/5085/6023R/6083R SNV-L5083R/L6083R 	<p>Wall Mount</p> <ul style="list-style-type: none"> Plastic Can be used with QND-7080R/7030R/7020R/7010R/6070R/6030R/6020R/6010R, XND-6010/6020 SND-L6083R/L6014R/L6013R/L6013/L6012/L5083R/L5013 SCD-6083R/6023R/6021/5083R/5083/5082/5080 (SBP-120WM) 	<p>Pole Mount</p> <ul style="list-style-type: none"> SECC Can be used with SBP-300B/300WM1/300WM/300LM (SBP-300PM) Can be used with PNO-9080R/SNO-8081R/SBO-100B1 QNO-7080R/6070R/7010R/7020R/7030R/6010R/6020R/6030R (SBP-302PM) 	<p>Corner Mount Base</p> <ul style="list-style-type: none"> SECC Can be used with SBP-300B/300WM1/300WM/300LM 	<p>Pole Mount</p> <ul style="list-style-type: none"> Stainless Steel 316 Can be used with SBP-300B/300WM1/300WM/300LM 	
 <p>SBP-300B</p>	 <p>SBP-300NB</p>	 <p>SBV-160WC</p>	 <p>SBV-120WC</p>	 <p>SBV-136B/158G</p>	 <p>SBF-100B1/SBO-100B1</p>
<p>Wall Mount Base</p> <ul style="list-style-type: none"> Aluminum + SECC Can be used with SBP-300PM/300KM 	<p>Installation Box</p> <ul style="list-style-type: none"> Steel Can be used with SBP-300WM/300WM1/300KM/300PM 	<p>Weather Cap</p> <ul style="list-style-type: none"> Alluminum and Poly Carbonate Can be used with PNV-9080R XNV-6080/6080R/8080R SCV-6081R/5084/5084R SNV-6084/6084R/6085R/7084/7084R/8080/8081R 	<p>Weather Cap</p> <ul style="list-style-type: none"> Alluminum and Poly Carbonate Can be used with XNV-6010/6020/8020R/8030R/8040R QNV-6010R/6020R/6030R/7010R/7020R/7030R 	<p>Back Box</p> <ul style="list-style-type: none"> Aluminum Can be used with SCV-5082/5082R/5083/5083R/5085/6023R/6083R SNV-L5083R/L6083R QNV-6070R/7080R (SBV-136B) Can be used with PNV-9080R SNV-5084/5084R/6084/6084R/6085R/7084/7084R/8080/8081R SCV-6081R (SBV-158G) 	<p>Back Box</p> <ul style="list-style-type: none"> Aluminum Can be used with PNF-9010R/9010RV/9010RVM SNF-8010/8010VM (SBF-100B1) Can be used with QNO-7080R/6070R/7010R/7020R/7030R/6010R/6020R/6030R SNO-L6083R/L5083R SCO-6083R (SBO-100B1) HCO-7070R/7010R/7020R/7030R/6080R/6070R

PERIPHERALS



SHB-4300H1/4300HP

- fixed Housing
- Aluminum diecasting construction
 - Fully cable managed bracket
 - Built-in fan & heater
 - Support three cable glands, IP66



SHB-4200/4200H

- fixed Housing
- Support two cable glands
 - Built-in fan & heater : SHB-4200H



STB-4150V

- fixed Mount
- Bracket for box cameras
 - Alluminum and Steel material



SPB-IND5

- Smoked Dome Cover
- Poly Carbonate + Poly Carbonate
 - Can be used with
SCD-6081R
SND-5083/5084/6083/6084/6084R/
7084



SPB-IND6

- Smoked Dome Cover
- Aluminum + Poly Carbonate
 - Can be used with
SCD-5080/5082/5083/5083R/6021/6083R
SND-6011R
SUD-5082



SPB-IND11

- Smoked Dome Cover
- Aluminum + Poly Carbonate
 - Can be used with
XND-6010/6020/8020R/8030R/8040R



SPB-IND12

- Smoked Dome Cover
- Poly Carbonate + Poly Carbonate
 - Can be used with
QND- 6010R/6020R/6030R/7010R/7020R/7030R



SPB-IND72

- Smoked Dome Cover
- Poly Carbonate + Poly Carbonate
 - Can be used with
QND-6070R/7080R



SPB-IND81V

- Smoked Dome Cover
- Aluminum + Poly Carbonate
 - Can be used with
XND-6080V/6080RV/8080RV



SPB-VAN3

- Smoked Dome Cover
- Aluminium + Poly Carbonate
 - Can be used with
PNV-9080R
SCV-6081R
SNV-5084/5084R/6084/6084R/6085R/
7084/7084R/8080/8081R
XNV-8080R/6080/6080R



SPB-VAN4

- Smoked Dome Cover
- Aluminium + Poly Carbonate
 - Can be used with
SCV-5082/5082R/5083/5083R/5085/
6023R/6083R
SNV-L5083R/L6083R



SPB-VAN11

- Smoked Dome Cover
- Aluminium + Poly Carbonate
 - Can be used with
XNV- 6010/6020/8020R/8030R/8040R



SPB-VAN12

- Smoked Dome Cover
- Aluminium + Poly Carbonate
 - Can be used with
QNV- 6010R/6020R/6030R/
7010R/7020R/7030R



SPB-VAN72

- Smoked Dome Cover
- Aluminium + Poly Carbonate
 - Can be used with
QNV-6070R/7080R

PERIPHERALS

PTZ Cameras







Type	Outdoor PTZ						Indoor PTZ				
Shape											
Color	Ivory										
Model	SCP-2270H/2330H/ 2370H/2370TH/ 3370H/3370TH/ SNP-3301H/3302H/ 3370TH/3371H/ 3371TH/ 5200H/5200TH/ 6200H/6200TH	SCP-2250H/2251H/ 2430H/3250H/ 3430H	SCP-3120VH SNP-3120VH	SCP-2271H/2273H/ 2371H/2373H/ 3371H SNP-5300H/5320H/ 5321H/5430H/ 6201H/6320H/ 6321H/L5233H/ L6233H HCP-6230H/6320HA	SCP-2370RH SNP-6200RH/6230RH/ L6233RH/6320RH	XNP-6370RH PNP-9200RH	SCP-2270/2330/ 2370/3370 SNP-3300A/3301/ 3302/3350/ 3370/3371/ 3750/5200/ 6200	SCP-2250/2251/2430/ 3250/3430	SCP-3120/2120 SNP-3120	SCP-2271/2273/ 2371/2373/ 3371 SNP-5300/5320/ 5321/5430/ 6201/6320/ 6321/L5233/ L6233 HCP-6230/6320A	XNP-6120

Coming Soon

Dome Cameras


Type	Vandal-Resistant						Indoor Dome					
Shape												
Color	Ivory											
Model	SCV-2060/2080/ 3080/3120 SNV-3080/3082/ 3120/5080/ 5080R/7080/ 7080R/7082	SCV-2081/2081R/ 2082R/3081/ 3082/3083 SNV-1080/1080R	PNV-9080R XNV-6080/6080R/ 8080R SCV-6081R SNV-5084/5084R/ 6084/6084R/ 6085R/7084/ 7084R/8080/ 8081R	SNV-6013 XNV-6011	QNV-6070R/7080R SCV-5082/5082R/ 5083/5083R/ 5085/6023R/ 6083R SNV-L5083R/L6083R HCV-6080R/6070R/ 7070R	QNV-6010R/6020R/ 6030R/7010R/ 7020R/7030R XNV-6010/6020/ 8020R/8030R/ 8040R HCV-7010R/7020R/ 7030R	SCD-2060E/2080/ 2080R/2081/ 2082/3080/ 3081/3082/ 3083 SND-1080/5061/ 7061	SCD-2020/2020R/ 2021/2022/ 2022R/2040/ 2042R/5010/ 5020/5030 SND-1011/5011/ 7011 SUD-2020/2022/ 5020	SCD-6081R SND-5083/5084/ 5084R/6083/ 6084/6084R/ 7084/7084R	QND-6070R/7080R SND-L5083R/6011R/ L6083R SCD-5080/5081R/ 5082/6021/ 6083R SUD-5082 HCD-6070R/6080R/ 7070R	QND-6010R/6020R/6030R/ 7010R/7020R/7030R/ SCD-6023R SND-L5013/L6012/ L6013/L6013R/ L6014R/ XND-6010/6020R/ 8020R/8030R/8040R HCD-7010R/7020R/7030R	PND-9080R XND-6080RV/6080V/ 8080RV

Fisheye / Panoramic Cameras

Type	Fisheye				Multi Imager	
Shape						
Color	Ivory					
Model	SNF-7010	SNF-8010	SNF-7010V/ 7010VM	PNF-9010R/ 9010RV/ 9010RVM SNF-8010VM	PNM-9020V HCM-9020VQ	PNM-9081VQ/ 9080VQ





ACCESSORIES CONFIGURATION

PTZ ACC




ACCESSORIES CONFIGURATION

DOMES ACC



ACCESSORIES CONFIGURATION

FISHEYE ACC




BULLET ACC




PRODUCT NAMING RULE


Camera




Decoder/Encoder



Recorder



Monitor



Hanwha Techwin America
500 Frank W. Burr Blvd. Suite 43 Teaneck, NJ 07666
Toll Free : +1.877.213.1222 Direct : +1.201.325.6920
Fax : +1.201.373.0124
www.hanwhasecurity.com

© 2017 Hanwha Techwin Co., Ltd. All rights reserved.

DESIGN AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE
Under no circumstances, this document shall be reproduced, distributed or changed,
partially or wholly, without formal authorization of Hanwha Techwin Co.,Ltd.

I.H-1707



Formerly Samsung Techwin